ASTRALPOOL



Fountains PROJECT & PRODUCT

CATALOGUE











the heart is the fountain of life.





Fountains

CATALOGUE

CONTENTS

WATER

- 008 Origin Where life is born
- 008 Values Associated with water
- 010 Meaning What water means for human beings
- 012 History The worship of water

FOUNTAIN

- 016 **Description and metaphor** What is a fountain?
- 018 History Synonymous with life since the beginning of time
- 022 Evolution Natural and artificial
- 022 Types Natural and artificial, decorative and functional

COMPANY

- 028 ASTRALPOOL Philosophy
- 034 About us Professionals
- 040 Facilities Our space
- 042 Projecting ideas Our inspiration
- 044 What we offer
- 048 **R&D** Research



PROJECTS

050 Some of our projects

PRODUCTS

140 **Customizable Fountains** Digital Curtain Digital Curtain App Funsquare Water Screen Water Curtain Water Curtain With Linear Led Waterfall Geyser Jet Plug & Play Dmx Variable Pump S Dmx Variable Pump L

152 Jets

Spear Nozzle **Big Spear Nozzle** Fan Jet Nozzle Cascade Nozzle Foamy Nozzle Foamy Hollow Nozzle 1" Fog Nozzle Vulcano Nozzle S Mushroom Nozzle Dancer Jet Swing Dancer Jet Dancer Nozzle Glassy Jet With Jumping Effect Glassy Jet Glassy Jet Without Light Rocket Jet Rocket Jet Horizontal Fire Jet Switch S System Switch L System Cosmos

184 Interaction Inmotion System Interactive Sensor Buttons

186 Illumination Nig projector Nano Projector Mini/Mini+ Projector Circular Ø200 Circular Ø300 Halospot Projector Kibele projector Linear Escala projector Adjustable Linear Projector Starry Sky effect Waterproof connection OnDMX control system OnDMX PRO control system DMX Driver Onled Power Supply DMX Driver Onled External Power Supply OnLED modulator OnLED remote control OnLED WiFi Access Point OnLED APP Power supply Safety transformers V:Nano V:Server3 Touch

222 Complementary Products Level Control System Wind Control System Pipe Fitting Cable Inlet Fitting 1 - 2" Female Thread Prefilter LFS Pressure Holding Valve Overflow Floor Drain Junction Boxes Cable Inlet Fitting Cable Inlet Fitting Box Electric Valves CPV Swivel LF filters HFL filters Victoria Plus Silent pump Kivu Pump Submersible Pump Df With Prefilter **Arals Strainers** Aster Filters Drain grille in stainless steel Breturn Inlet Waterproof Junction Optima Next Controller 3.5 kg Dossi-3 Dossi-5 Power Signal UV **Buster UV-C Units**



WATER

When you drink water, remember the source.

WATER / ORIGIN & VALUES

WHERE LIFE IS BORN

Water is the source of everything. Nothing as we know it would exist without it. Animals, plants, our very lives would be impossible were it not for water, a substance that covers over 70% of the earth's surface in its three states: liquid, solid and gas.

Liquid, transparent, odourless, colourless and tasteless: all living beings need water to survive.

ASSOCIATED WITH WATER

Water is inspiration, peace, harmony. It is a source of beauty and calm.

It flows in rivers, is still in lakes and unleashes its fury in the seas and oceans.

Water extinguishes fire, but supports life.









MEANING / WATER

WHAT WATER MEANS FOR HUMAN BEINGS

Water has been here since the beginning of time, and yet we have always sought it out. All living beings have based their existence on the search for water, settling near water sources (rivers, lakes, seas) or diverting these sources to their settlements. Because water is vital, essential, and nothing would exist without it.

How was life created?

The question remains unanswered.

But what supports life? The answer is easy: water. WATER / HISTORY

THE WORSHIP OF WATER

Symbol of purification and an expression of the sacred, water is the fountain of life. It is associated with medicinal and healing qualities.

Water plays a fundamental role in all religions and beliefs, inspiring both worship and respect.

Tales de Mileto:

"Water is the origin of everything that exists. It is the essential element"







A fountain is generally synonymous with life.

FOUNTAIN / DESCRIPTION AND METAPHOR

WHAT IS A FOUNTAIN?

A fountain is, without doubt, an expression of the beginning, the origin of things. A source of light, water, information or energy is always the beginning.

Like a spring of water welling up from the earth, the fountain is the source of rivers that cross mountains to end their journey flowing into the sea.

Fountain. the source or origin of anything.











HISTORY / FOUNTAIN

SYNONYMOUS WITH LIFE SINCE THE BEGINNING OF TIME

Fountains have always been synonymous with life, playing a vital role as a source of happiness, a place where communities gather, a vibrant and dynamic space, a meeting point and a metaphor for life.







FOUNTAIN / EVOLUTION & TYPES

NATURAL AND ARTIFICIAL

Since the dawn of time man has sought to control his environment; water, the planet's dominating element, is one of the elements that man has mastered best. A desire to bring water closer to people resulted in the first fountains, which were typically located in the village centre. Over time and with the development of new materials, the original more functional purpose of these fountains shifted towards a more decorative one, each fountain becoming a unique and spectacular piece.

NATURAL AND ARTIFICIAL, DECORATIVE AND FUNCTIONAL

Today we can enjoy fountains as a more decorative, participatory and spectacular element.











ASTRALPOOL

ASTRALPOOL A fountain of ideas.

COMPANY / ASTRALPOOL

PHILOSOPHY

ASTRALPOOL, with over 40 years of experience, is the leading brand in the world of swimming pools and ornamental fountains.

The ASTRALPOOL trademark is sold in over 150 countries. It directly sells its products in 45 countries through a network of companies owned by Fluidra, comprisin a total of 130 subsidiaries, warehouses and branch offices. Over 55.000 professionals and 200.000.000 pools use one of our 15.000 products.

Completely innovative and sustainable solutions

Over and above functionality, the products and solutions offered by ASTRALPOOL deliver sustainable responses that enable users to save water and look after the environment while they enjoy their pools and ornamental fountains.

For all of these reasons and many more, our systems and components for residential and commercial pools and fountains are and will continue to be world leaders. We set the benchmark for professionals and private home owners.

Let ASTRALPOOL surprise you once again.

"AstralPool takes a technical approach to the analysis of each project, delivering solutions that make installation and maintenance easier"







CLIENT CONNECTION

The ASTRALPOOL philosophy has always been to assist clients throughout the entire decision-making process. By providing a friendly and attentive service ASTRALPOOL seeks two-way communication and strives to make a connection with clients, always with an approach that best ensures a positive outcome. Client care, advisory services, dialogue and commitment are some of the keys to our success.

ASTRALCARE

ASTRALPOOL closely monitors each project every step of the way. Work is managed and supervised throughout the design, construction, installation and commissioning processes to ensure the utmost rigour and professionalism. Client communication is crucial for making monitoring as easy as possible, tailored to each project's needs.

ENGINEERING&RESEARCH

ASTRALPOOL has always been strongly committed to innovation and creativity. Taking a more creative approach to new projects, we work with the industry's most cutting-edge technology, researching new decorative systems and optimal solutions to create the most innovative effects.

CONCEPT DESIGN

Our work is focused on making unique fountains that reflect each client's individual concept. We transform water into architecture, blending water and nature to create dynamic shapes that integrate into the urban environment.



ANIMATION

To make it easier to evaluate designs, choreography and urban integration, ASTRALPOOL employs 3D animation to give clients a clearer picture of what the final results will look like. This makes it possible to quickly and visually understand the concept, creating an opportunity for clients to suggest changes to better adapt the project to their vision.

COREOGRAPHY

Ultimately, a fountain's most visible element are the movements of water and light. Choreography and sequences that feature water, music and light provide a colourful, dynamic and eye-catching show.

These movements are designed by ASTRALPOOL's experts, who supervise and manage every aspect of the choreography and sequences. As if it were a dance, a ballet: we believe that every water show is unique.

MANUFACTURING

Our technical team develops and manufactures most of the material, which is tailor-made for each project. Each fountain is a new challenge and therefore requires a customised design in which each piece is developed and adapted to the project's particular requirements. This ensures that each design fits the client's needs and vision.

INSTALLATION&COMISSIONING

To ensure that each project runs smoothly, ASTRALPOOL relies on an expert team of technicians who handle the end-to-end installation of new fountains, from properly installing all machinery to setting up all the electrical programming prior to the fountain's commissioning. This guarantees a flawless installation from start to finish.

COMPANY / ASTRALPOOL





COMPANY / ABOUT US

PROFESSIONALS

The success of ASTRALPOOL is based on the knowledge and experience of our professionals. Each and every team member contributes and projects ideas, solutions and resources that daily enhance the solutions we propose.

Every challenge, every new project is a reason to improve and implement those solutions, those small details that enhance the product and help to evolve and grow our vision of what business means.

"Each fountain is practically handcrafted, every detail matters"




"We design projects with a forward-looking approach, that are sensitive to the environment and adapt to its needs"





























COMPANY / FACILITIES

OUR SPACE

"Our modern facilities make it possible for us to plan, study and execute each of our products"





COMPANY / PROJECTING IDEAS

OUR INSPIRATION

ASTRALPOOL mission is to drive society's progress through the sustainable use of water in its range of recreational, domestic and industrial applications.

Water is what we are all about and, as a result, all of ASTRALPOOL's activities are based on the commitment to its responsible use. Savings on costs and reuse of resources underpin any line of action the Group pursues and serve as the basis for product development.

We are committed to promoting the responsible use of water and the rigorous application of sustainability criteria for future generations. We have the ability to adapt with ease, efficiency and rigour, projecting our ideas in an environment we respect and strive to improve.





COMPANY / WHAT WE OFFER

WHAT WE OFFER

We offer "Water Solutions" for ornamental Fountains, Swimming Pools, Wellness Areas and Lagoons for cities, shopping malls, hotels & resorts, urban spas and fitness clubs.

Water solutions for a unique experience

GLOBAL PRESENCE

We are one of Spain's largest industrial groups with a global presence. We have our own production centres and a distribution network that operates on five continents.

"global presence is our biggest challenge and project for the future"



FLUIDRA ENGINEERING SOLUTIONS

Fluidra Engineering has an expert team with extensive experience in concept, design and implement international aquatic projects.

It offers complete solutions by applying its own products and working in an integrated manner with its clients.



FOUNTAINS

AQUARIUMS

WATER PARKS

COMPETITION

FLUIDRA ENGINEERING SERVICES

As a "Solution Partner", Fluidra is able to manage a project from the preliminary consultancy all the way to project architecture and design, project engineering and management, equipment manufacturing and distribution.

Fluidra also helps in planning and implementing bespoke solutions, designed by architects and designers.

C	9

PRELIMINARY CONSULTANCY

- Conceptualization
- Preliminary design
- Budget estimation

ENGINEERING AND DESIGN

- Basic project
- Executive project
- Equipment sizing and calculation
- Advice on water care
- Innovative solutions & technological development
- BIM (Building Information Modelling)
- Computational Fluid Dynamics (CFD)
- Fluidra Virtual reality



EQUIPMENT MANUFACTURING

- 37 manufacturing facilities
- State-of- the art technology
- Automated logistic operator
- Quality certifications



PROJECT MANAGEMENT ANDEXECUTION

- Project planning and coordination
- Installation of complete solution
- On site Project Manager
- After sale support



COMPANY / WHAT WE OFFER

YOUR WATER SOLUTION PARTNER

Working with Fluidra, specialized in water projects and manufacturing of all the necessary equipment, is a safe and attractive option. With Fluidra, you have a specialist at your disposal as a single point of contact throughout the process. This makes the planning and implementation of tailor-made solutions easier, while ensuring the respect of the deadlines and the budget estimations.

"More than 50 years of history"



MULTIDISCIPLINARY

R+D+l center that focuses on sustainable solutions.

(HQ)

MANUFACTURING

37 Manufacturing sites in key markets



LOGISTICS

Logistics operators to ensure fast and reliable deliveries.



136 points of sale, giving support and training to professional clients in 46 countries.

ENGINEERING

M

Design and engineering of water projects.



INSTALLATIONS

More than 1,5m private and public completed projects.







RESEARCH

We promote a culture of innovation with enthusiasm and creativity in order to meet new challenges

R&D&I is the foundation of our competitiveness. Using the cleanest and most efficient technologies possible, along with developing products based on the environmentally sustainable use of water, are the main focus of the Group's innovation policy.





OUR PROJECTS

Dream, Do, Grow,





















PROJECT /

In ASTRALPOOL we have worked with some of the most worldwide know Architecture offices, collaborating in the design of the fountains, creating new products and adapting the technologies in order to find solutions for each project.

We have participated in all the stages of the project, from the fist thought and design, to the basic and executive projection of the fountain, the manufacturing, supervision/ installation, commissioning and choreography to get the best results.

I would like us to attach importance to things again



PROJECT /

Great Exhibition of the North

– Newcastle, United Kingdom







Great Exhibition od the North

. .

_ 0

F

-

田

PROJECT /

Kashirskaya – Mocow, Russia





Kashirskaya

-

C

PROJECT /

Vadi Istanbul – Istanbul, Turkey







Vadi Istanbul

_ _

Central Park – Almaty, Kazakhstan



PROJECT /



Central Park

The Harbor Merida – Merida, Mexico



PROJECT /







The Harbor Merida

Isataya Square – Atyrau, Kazakhstan





PROJECT /



Funsquare in Lodz – Lodz, Poland





PROJECT /



Funsquare in Lodz

PROJECT / Nazarbaev Street Funsquare – Almaty, Kazakhstan








Nazarbaev Street Funsquare

71

Boscolo Airone Hotel – Venice, Italy









Boscolo Airone Hotel

Nazarbaev Street Vessel Fountain – Almaty, Kazakhstan



Nazarbaev Street Vessel Fountain

PROJECT / Almaty Shell Fountains – Almaty, Kazakhstan





Almaty Shell Fountains

S

Astana Expo 2017 – Astana, Kazakhstan











Astana Expo 2017

PROJECT / Gravellona Toce – Verbano-Cusio-Ossola, Italy





Gravellona Toce

Souq Waqif Funsquare – Doha, Qatar



ARCHITECT / GHARNATA CONSULTANT ENGINEERS





Souq Waqif Funsquare

Gharnata Consultant Engineers

PROJECT /

Mega Silk Way – Astana, Kazakhstan





La Pedrera Park – San Luis, Argentina







La Pedrera Park

-

WEEKS

Style Outlets Viladecans – Barcelona, Spain



ARCHITECT / BATLLE I ROIG ARQUITECTES





Style Outlets Viladecans

Batlle i Roig Arquitectes

Moremall Fountain – Sochi, Russia



ARCHITECT / PAVEL KAMYSHNIKAU





Moremall Fountain

Pavel Kamyshnikau

PROJECT / Catalonia Square Fountains – Barcelona, Spain



ARCHITECT / CARLES BUÏGAS

ASTRALPOOL 🛆



Catalonia Square Fountains

Carles Buïgas

PROJECT / Timisoara Sunsquare – Timisoara, Romania











Panama City – Panama









Ciudad de los Niños Park – Almeria, Spain



ARCHITECT / INTEGRA ARQUITECTURA



PROJECT /

Park de les Rieres d'Horta Funsquare

Barcelona, Spain









ARCHITECT / CARLES CASAMOR

Park de les Rieres d'Horta Funsquare

Carles Casamor

PROJECT / Plaisance-du-Touch Funsquare – Toulouse, France





PROJECT / Taman Anggrek Funsquare – Jakarta, Indonesia







Slavyansky Shopping Mall – Moscow, Russia



ARCHITECT / PAVEL KAMYSHNIKAU



Slavyansky Shopping Mall

Pavel Kamyshnikau

Baku Geyser (140 m) – Baku, Azerbaijan





Baku Geyser (140 m)



Shamkir Park – Shamikir, Azerbaijan



ARCHITECT / MDM GROUP


Puerto Venecia – Zaragoza, Spain



ARCHITECT / L35 ARCHITECTS



.35 Architects

Yeni Hayat Mall – Baku, Azerbaijan



ARCHITECT / TASARIM MIMARLIK



Diagonal Mar Park – Barcelona, Spain

PROJECT /



ARCHITECT / ENRIC MIRALLES

Zenia Boulevard – Orihuela, Spain





ARCHITECT / RTKL ARCHITECTS



-

Zenia Boulevard

RTKL Architects

Madrid Rio Fountains – Madrid, Spain



ARCHITECT / WEST 8 ARCHITECTS



------10000 ħ 10.00 (and the second THE OWNER A. C. MARCO

Madrid Rio Fountains

Sollie.

West 8 Architects

La Pegaso Park - Barcelona, Spain







España Industrial Park – Barcelona, Spain





España Industrial Park

1

and Hannell

Fira de Barcelona Fountains – Barcelona, Spain





Fira de Barcelona Fountains

STRALPOOL

10.000

Toyo Ito

Barris Central Park – Barcelona, Spain





ARCHITECT / ARRIOLA&FIOL ARCHITECTS

122



Barcelona Parc Central

5 10 m

300 000 000 000 0000

.....

Arriola&Fiol Architects

Constitution Square – Lleida, Spain





PROJECT /

France Square – Lleida, Spain





Central Square – Dimitrovgrad, Bulgaria





La Pau Square – Lleida, Spain



ARCHITECT **/ CARLES BUÏGAS**



La Roca Village Mall – Barcelona, Spain

PROJECT /



ARCHITECT / L35 ARCHITECTS

Sant Adria de Besos Funsquare

Barcelona, Spain







Sant Adria de Besos Funsquare

Gran Via Waterfall – Barcelona, Spain



Gran Via Waterfall

- 104/2000

ASTRALPOOL

Lesseps Square - Barcelona, Spain









Sant Julià de Ramis Funsquare

Sant Julià de Ramis, Spain



Torre Agbar Waterfalls - Barcelona, Spain



ARCHITECT / JEAN NOUVEL



PROJECT /

Rehabilitations of Classical Fountains







PRODUCT DETAILS

Discover them all.

* We reserve the right to change product features and the contents of this document without prior notice.

CUSTOMIZABLE FOUNTAINS DIGITAL CURTAIN



* Product Upon Request

PROJECT VIEW



Historically, murals have been a way of representing all kind of elements. Through a combination of water and light, these representations will be given a new meaning in an innovative and interactive way.

The effect introduces new technologies able to represent shapes instantly by interacting with a tablet device. A multitude of geometric combinations, organic figures and texts have their place within the concept of an interactive curtain, where you can draw and create anything you want using water and light.

Due to the force of gravity, it is important to highlight that the recommended height is lower than 4 meters. The Digital Curtain is perfect for advertising.

DIGITAL CURTAIN Code: 66548	
Dimensions (L x W x H) [mm]	1035 × 390 × 393 (standard)
Nominal Voltage [V]	230 VAC
Light type	RGB+W - DMX
Light power consumption [W/m]	52
Total power consumption [W/m]	240 (without pump)
Power rating[A]	1,1
Recommended pressure [bar]	0,5
Curtain flow [(m3/h)/m]	ų
Recommended height[m]	≤ 4
Control system	Watercurtain Manager Software
Material	AISI 316 / Brass / Others
Weight without water [kg/m]	58 kg/m
Weight with water [kg/m]	73 kg/m
Protection class	IP 66

DIGITAL CURTAIN



This exclusive application for tablets and mobile phones allows complete and real-time interaction with the digital curtain (66548).

Through the application, the user can send text, existing images of the preprogrammed gallery or even create new pictures. It is available for Android and iOS devices.

DIGITAL CURTAIN APP	Code: 66549
Curtain connection	WIFI
Availability in Android	YES
Availability in iOS	YES



CUSTOMIZABLE FOUNTAINS



PROJECT VIEW



CUSTOMIZABLE FOUNTAINS **FUNSQUARE**



PROJECT VIEW



Designed to be a fun area for the whole family, Funsquare comprises numerous high-speed, interactive vertical jets. It performs a sequence of ornamental and dancing effects that seem to be totally random. Wherever the Funsquare is located, it attracts people.

This effect not only seems to bring water and light to life, but the music also plays a key role creating magical dances. There are a number of sensors, such as weight, presence and pressure sensors, as well as ropes and cameras, all of which add even more interactivity and variations to the water features. Ask us about them!

4 × 4 × 0,6 others upon request
RGB - DMX
24 VDC
230 VAC
Depending on the size
10 - 19
4
DMX
DMX / PLC
AISI 316 stainless steel/Others
Depending on the size
IP 68

FUNSQUARE


This ornamental effect creates a large screen of water that serves as a perfect surface on which to project videos and other images. The Water Screen is big enough to project a standard panoramic HDTV image (16:9). The combination of this decorative feature with a video or laser projector will create a visually impressive effect.

WATER SCREEN Code: 66550	
Dimensions (L x W x H) [mm]	925 × 518 × 803
Inlet connection	Flange DN150
Screen dimensions range [m]	24 × 8 - 48 × 16
Flow range [m3/h]	110 - 260
Pressure range [bar]	6 - 12
Maximum water depth [mm]	530
Material	Stainless steel 316
Weight [kg]	94

CUSTOMIZABLE FOUNTAINS



WATER SCREEN





PROJECT VIEW





CUSTOMIZABLE FOUNTAINS WATER CURTAIN



This ornamental effect creates a large screen of water that serves as a perfect surface on which to project videos and other images. The Water Curtain is big enough to project a standard panoramic HDTV image (16:9).

The combination of this decorative feature with a video or laser projector will create a visually impressive effect.

WATER CURTAIN Code: 66551	
Dimensions (L x W x H) [mm]	1000× 140 × 114 (standard)
Recommended pressure [bar]	0,5
Curtain flow per m [m3/h]	4
Recommended height [m]	≤ 4
Material	AISI 316 stainless steel/Brass
Weight without water [kg/m]	15 kg/m
Weight with water [kg/m]	20 kg/m

* Product Upon Request

PROJECT VIEW



WATER CURTAIN



This ornamental effect creates a large screen of water that serves as a perfect surface on which to project videos and other images.

It incorporates RGB+W LED lighting with individual control of four LED lights each meter of water curtain, through DMX protocol.

The combination of the waterfall with integrated lighting will create a visually impressive effect.

WATER CURTAIN WITH LINEAR LED Code: 73346

Dimensions (L x W x H) [mm]	1042 × 164 × 114 (standard)
Nominal Voltage [V]	24 VDC
Light type	RGB+W - DMX
Power consumption [W/m]	52
Recommended pressure [bar]	0,5
Curtain flow per m [m3/h]	4
Recommended height [m]	≤ 4
Material	AISI 316 stainless steel/Brass
Weight without water [kg/m]	18 kg/m
Weight with water [kg/m]	23 kg/m

CUSTOMIZABLE FOUNTAINS WATER CURTAIN



ASTRALPOOL



WATER CURTAIN WITH LINEAR LED





CUSTOMIZABLE FOUNTAINS WATERFALL



This ornamental feature produces a continuous waterfall. As a result, it makes the gentle, calming sound of the waves on the beach. It can be installed both indoors and outdoors.

Its cutting-edge design creates a perfectly uniform film of water along the whole cascade.

It is made of AISI 316 stainless steel to ensure maximum resistance to rust and to give it a high quality finish.

It is possible to enhance the ornamental effect by adding a lighting system.

WATERFALL Code: 66552	
Dimensions (L x W x H) [mm]	2000 × 385 × 296 standard, others on request
Fall pressure (max.) [bar]	0,5 (low pressure recommended)
Flow per m [(m3/h)/m]	12,5 (e=15mm)
Maximum flow [(m3/h)/m]	30
Material	AISI 316 stainless steel
Weight [kg]	25

PROJECT VIEW





WATERFALL







A large water jet, both impressive and imposing, is the effect you get with a Geyser. As if it were a natural geyser, a large amount of water is pumped up at a high altitude to form part of the skyline.

Combined with the appropriate lighting system, the Geyser is a great visual image that can be seen from great distances, thus becoming a landmark in the landscape.

This ornamental fountain can be placed in freshwater, seawater and in the open sea on a fixed or floating structure.

GEYSER JET

Dimensions (L x W x H) [m]	Depending on the size
Nominal voltage [V]	400 VAC
Power [W]	Depending on the size
Jet diameter [mm]	Upon request
Jet height [m]	Upon request
Material	AISI 316 stainless steel
Weight [kg]	Depending on the size
Protection rating	IP 68

CUSTOMIZABLE FOUNTAINS **GEYSER** JET

* Product Upon Request

GEYSER JET



PROJECT VIEW



CUSTOMIZABLE FOUNTAINS **PLUG & PLAY**



The Plug and Play fountain kit let you have a small complete fountain into your garden.

It combines comfort, design and energy efficiency in a easy and quick product to install.

It comes with 10 meter cable, a nozzle and a multicolor RGB light included. The nozzle can be replaced by any other nozzle of our plug and play series to configure the fountain to your preference.

The highly efficient RGB LED with color changing sequence brings color into the pond.

The jet height is adjustable up to 3.5 meters, according to the installed nozzle.

PLUG & PLAY	66979 KIT SPEAR D12	66980 KIT FOAMY 35	66981 KIT VULCANO	66982 KIT MUSHROOM
Dimensions (L x W x H) [mm]	281 × 218 × 390	281 × 218 × 434	281 × 218 × 354	281 × 218 × 565
Connection	1" G	1" G	1" G	1" G
Nozzle material	Stainless Steel 304	Plastic / Stainless Steel 304	Stainless Steel 316	Stainless Steel 316
Pump	24 VDC / 105 W (Power supply included)			
LED lighting	12 VAC / 4 W (Transformer/ select button included)			
Max. Height	2,5 m	1 m	2 m	1 m (Diameter)











Plug & Play Customizable Fountains

PROJECT VIEW .





66981 PLUG & PLAY KIT VULCANO



66980 PLUG & PLAY KIT FOAMY



CUSTOMIZABLE FOUNTAINS DMX VARIABLE PUMP S



PROJECT VIEW



NEW PRODUCT

The DMX Variable Pump S allows to control the jet heights individually, creating a multitude of effects and figures in dynamic fountains. It is ideal to be installed just below the Spear Nozzle between 12 and 14 mm and Foamy Nozzles.

The device incorporates the height variation system through DMX protocol, what facilitates the control of the jets and reduces considerably the size and cost of electrical cabinets

Dimensions (L x W x H) [mm]	254 × 97 × 121
Nominal voltage [V]	24 VDC
Power [W]	100
Power raring [A]	4,2
Hydraulic connection	1-1/2" G
Minimum water depth [mm]	200
Maximum pressure [m]	5
Maximum flow [l/min]	160
Dynamic response 0-100% [s]	1
Starts per minute (max.)	6
Control system	DMX-RDM
Weight [kg]	2

DMX VARIABLE PUMP S





The DMX Variable Pump allows to control the height of the jets individually, creating a multitude of effects and figures in dynamic fountains. It is ideal to be installed just below the Spear Nozzle between 12-20 mm and Foamy Nozzles.

The device incorporates the height variation system of variation through DMX protocol, what facilitates the control of the jets and reduces considerably the size and cost of the electrical cabinets.

DMX VARIABLE PUMP L Code:	67411
Dimensions (L x W x H) [mm]	500 × 366 × 239
Nominal voltage [V]	220 - 240 VAC
Power [W]	720
Power raring [A]	3,7
Hydraulic connection	1-1/2" G
Minimum water depth [mm]	300
Maximum pressure [m]	11
Maximum flow [l/min]	320
Dynamic response 0-100% [s]	1
Starts per minute (max.)	6
Control system	DMX (1 channel)
Material	Stainless steel
Weight [kg]	23

DMX VARIABLE PUMP L



CUSTOMIZABLE FOUNTAINS







JETS SPEAR NOZZLE

Big Spear Nozzle is a nozzle designed for ornamental fountains with great height jets.

Those are entirely made of AISI 316 stainless steel, which provides high sturdiness and oxidation resistance, and provides a stylish finish to the fountain. They can be made of brass material on request.

It has a $10^{\rm o}$ adjustable joint to correct the jet outlet in case of misalignment of manifolds or pipes.

NOZZLE		NOZZLE 4	SPEAR I		SPEAR I	NOZZLE 3	SPEAR 1			NOZZLE 2	SPEAR I 1			NOZZLE 6		NOZZLE 20
Code	67 ¹	496	666	539	666	640	660	541	66	642	666	543	66	644	60	6645
Inlet	G 3/	/8" M	G 3/	8" M	G 1/	2" M	G 1/1	2" M	G1	" М	G1	"М	G 1-1	/2" M	G 1-	1/2" M
Jet diameter	Ø 4	mm	Ø6	mm	Ø 8	mm	Ø 10	mm	Ø 12	? mm	Ø 14	mm	Ø 18	, mm	Ø2	20 mm
Dimensions ØCxB	Ø21×8	52 mm	Ø21×5	52 mm	Ø24×7	76 mm	Ø24×7	76 mm	Ø36×	111 mm	Ø36×1	111 mm	Ø61×1	67 mm	Ø61×	167 mm
Jet height [m]	l/min	m	l/min	m	l/min	m	l/min	m	l/min	m	l/min	m	l/min	m	l/min	m
0,5	2,4	0,6	4,9	0,6	9,6	0,7	15,8	0,8	25,4	1,0	31	0,9	46	1,0	70	1,2
0,75	2,9	1,0	6,1	0,9	11,6	0,9	19,3	1,1	30,2	1,3	38	1,2	55	1,3	80	1,3
1	3,4	1,2	7,2	1,2	13,3	1,3	21,9	1,4	33,6	1,5	44	1,4	62	1,5	87	1,5
1,25	3,8	1,5	8,5	1,4	15,9	1,6	24,8	1,7	39,0	2,0	51	1,8	70	1,9	95	1,8
1,5	4,2	1,8	9,6	1,7	17,1	1,8	27,8	2,0	40,9	2,1	55	2,1	76	2,1	104	2,1
1,75	4,7	2,3	11,0	2,0	19,5	2,1	32,0	2,4	45,8	2,6	61	2,4	82	2,4	111	2,4
2	4,9	2,7	11,6	2,4	20,4	2,4	32,4	2,7	46,6	2,7	65	2,7	88	2,6	119	2,7
2,5	5,4	3,1	13,2	3,0	23,2	3,1	36,6	3,4	51,9	3,2	72	3,3	99	3,2	135	3,3
3	6,1	3,6	14,7	3,7	25,8	3,7	40,3	4,1	57,2	3,8	81	4,0	108	3,7	148	4,0
3,5	6,6	4,2	15,6	4,3	28,1	4,4	44,3	4,8	62,9	4,5	88	4,7	117	4,5	160	4,6
4	7,2	4,9	16,5	5,0	30,3	5,0	48,6	5,6	66,4	5,0	94	5,3	125	5,1	171	5,2
5			• • •		35,0	6,1	54,8	7,1	75,1	6,2	107	6,6	138	6,0	197	6,4
6			• • •		• • •		60,4	8,6	83,9	7,5	118	7,9	150	7,5	217	7,6
7			• • •		• • •				91,7	8,6	129	9,3	164	8,5	238	8,9
8			• • •		• • •				98,2	9,8	139	10,5	176	9,6	257	10,2
9					• • •		• • •				149	11,8	187	11,2	274	11,3
10					• • •		• • • • • • • • • • • • • • •				156	13,1	198	12,5	290	12,6
11			• • •		•								208	13,8	306	13,9
12			•		•								216	14,6	322	15,1
14	* *		•		•		•		9 9 9		0 0 0		•		348	17,6









Spear Nozzle

Jets





Big Spear Nozzle is a nozzle designed for ornamental fountains with great height jets.

Those are entirely made of AISI 316 stainless steel, which provides high sturdiness and oxidation resistance, and provides a stylish finish to the fountain. They can be made of brass material on request.

It has a 10° adjustable joint to correct the jet outlet in case of misalignment of manifolds or pipes.

NOZZLE	BIG SPEAR	NOZZLE 25	BIG SPEAR	NOZZLE 38	
Code	666	646	66647		
Inlet	G 2-1	/2" F	G۲	+" F	
Jet diameter A	Ø 25	mm	Ø 38	3 mm	
Dimensions BxC	317×14	5 mm	463×20	05 mm	
Jet height [m]	l/min	m	l/min	m	
10	440	13,5	895	13,0	
12,5	485	17,0	990	16,5	
15	550	20,0	1110	19,5	
20	615	27,5	1300	26,0	
25	680	34,0	1440	32,0	
30	760	42,0	1625	39,0	
35	810	48,0	1760	46,0	
40	865	55,0	1850	52,0	
50	970	65,0	2080	65,0	

PROJECT VIEW





BIG SPEAR NOZZLE



Fan Jet Nozzle produces a wide range of water that simulates a waterfall. It can be installed in vertical or inclined position, generating two different ornamental effects.

The ornamental effect doesn't depend on the level of water.

They are entirely made of AISI 316 stainless steel, which provides high sturdiness and oxidation resistance, and provides a stylish finish at the fountain.

NOZZLE	FAN JET N	OZZLE 4	FAN JET NO	OZZLE 6	
Code	666	95	66696		
Inlet c	G 1'	' M	G 1-1/2	" M	
Nozzle orifice	4×85	mm	G 1-1/2	" M	
Dimensions AxB	165×8	8 mm	5×100	mm	
JET HEIGHT [m]	l/min	m	210×103mm	m	
0,25	59	0,4	87	0,4	
0,5	78	0,6	120	0,8	
0,75	90	1	145	1,2	
1	107	1,2	165	1,6	
1,5	131	1,8	208	2,4	
2	160	2,5	241	3,2	
Jet LxH 45º [m]	III 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		· · · · · · · · · · · · · · · · · · ·		
0,5 × 0,1	65	0,4	74	0,4	
0,75 × 0,15	89	0,8	92	0,6	
1 × 0,2	103	1	115	0,8	
1,5 × 0,3	130	1,2	142	1,2	
2 × 0,4	156	2,3	174	1,5	
2,5 × 0,6	190	3,5	200	1,8	

jets **FAN JET** NOZZLE



FAN JET NOZZLE



PROJECT VIEW



JETS CASCADE NOZZLE

Cascade Nozzle is a classical jet that mixes water and air creating a solid and conic column of water visible from any direction. Furthermore contributes to an oxygen enrichment of the water.

Those nozzles are water level depending, so must be installed on a determinate height. Strong waves can cause abrupt changes in the height of the jet.

They are entirely made of AISI 316 stainless steel, which provides high sturdiness and oxidation resistance, and provides a stylish finish at the fountain.

NOZZLE	CASCADE	NOZZLE 35	CASCADE	NOZZLE 50	CASCADE I	NOZZLE 80	CASCADE N	NOZZLE 100	CASCADE	NOZZLE 12
Code	660	691	66692		66693		66694		66698	
Inlet D	G 1/	2" H	G 1	" H	G 1-1,	G 1-1/2" H		G 2" H		I/2" H
Jet diameter A	Ø 35	mm	Ø 50) mm	Ø 80	mm	Ø 100) mm	Ø 129	5 mm
Dimensions BxC	110×4	8 mm	140×6	6 mm	185×10)4 mm	261×12	?5 mm	298×145 mm	
Water level E	20 ו	mm	25 ו	mm	30 r	nm	35	mm	40 mm	
Jet height [m]	l/min	m	l/min	m	l/min	m	l/min	m	l/min	m
0,5	16	7,4	36	2,6	64	2,1	130	2,3	• • • • • • • • • • • • • • • • • • •	
0,75	19	9,8	43	3,5	78	2,9	144	2,9	• • • • • • • • • • • • • • • • • • •	
1	22	12,8	48	4,4	89	3,7	155	3,6	241	3,7
1,5	28	18,6	58	6,1	109	5,4	186	5,3	291	5,0
2	32	24,0	66	7,8	124	7,2	210	6,8	332	6,3
2,5			75	11,1	136	8,7	231	8,1	368	7,7
3	•		81	14,6	148	10,5	250	9,5	400	8,9
4	•		87	17,5	168	13,6	276	12,3	458	11,4
5	•		96	20,4	182	16,0	321	15,1	509	14,2
6			•		195	19,1	348	17,9	555	16,5
7			•		207	22,9	378	21,1	600	19,0
8	•				220	26,4	402	24,2	646	21,7
10					238	31,1	446	29,2	722	27,0
12					• • •		465	33,5	783	32,2
14			• • •		• • •		474	37,0	847	38,1
16	· · ·		0 0 0 11 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		• • •		• • •		901	42,6
18	• •		*		•		*		969	47,7







Cascade Nozzle

Jets





Foamy Nozzle produces a very sparkling and consistent jet. The ornamental effect doesn't depend on the water level and it's very wind resistant, generating a great uniformity on the fountain.

Furthermore, it contributes to an oxygen enrichment of the water.

They are made entirely of AISI 316 stainless steel, which provides high sturdiness and oxidation resistance, and provides a stylish finish at the fountain.

NOZZLE	FOAMY N	OZZLE 35	FOAMY N	OZZLE 50	FOAMY NOZZ	ZLE 35 PL/SS
Code	666	89	666	590	713	35
Inlet C	G 1	" M	G 1	" M	G 1'	" M
Jet diameter	Ø 35	mm	Ø 50) mm	Ø 32	mm
Dimensions AxB	53×15	5 mm	90×15	6 mm	60×15	8 mm
Jet height [m]	l/min	m	l/min	m	l/min	m
0,25	45	1,7	96	2,2	44	0,9
0,5	56	2,1	119	2,9	59	1,3
0,75	71	2,9	140	3,6	68	1,9
1	80	3,4	158	4,5	76	2,5
1,5	96	4,6	193	6,3	93	3,9
2	108	5,4	226	8,2	107	5
2,5	118	6,6	249	10	121	6,4
3	•		270	11,7	132	7,8
3,5	•		287	13,4	142	8,7
4	· · · · · · · · · · · · · · · · · · ·		302	15,1	· · · · · · · · · · · · · · · · · · ·	
4,5			314	16,9		
5	*		338	18,7		

FOAMY NOZZLE 35 Code: 66689



FOAMY NOZZLE 50 Code: 66690



FOAMY NOZZLE 35 PL/SS Code: 71335





Foamy Nozzle

Jets







JETS **TFE** NOZZLE

TFE Nozzle produces a sparkling and consistent jet with less flow requirements to similar nozzles with the same diameter. The ornamental effect doesn't depend on the water level and It Is very wind resistant, generating a great uniformity on the fountain.

It is made entirely of AISI 316 stainless steel, which provides high sturdiness and rusting resistance, and provides a stylish finish at the fountain.

TFE NOZZLE	TFE25 N	IOZZLE	TFE32 N	IOZZLE	TFE40 N	OZZLE
Code	724	-75	724	-76	72 ^L	+77
Inlet C	G 1'	" M	G 1 1/	′4" H	G 1 1,	/2" H
Jet diameter	Ø 25	Ø 25 mm		Ø 32 mm	Ø 40 mm	
Dimensions AxB	155×3	8 mm	173×4	3 mm	210×5	3 mm
Jet height [m]	l/min	m	l/min	m	l/min	m
0,5	30	1,1	45	1,4	61	1,8
1	38	1,8	56	2,3	74	2,8
1,5	47	2,6	69	3,3	90	4,0
2	52	3,5	79	4,3	105	5,4
2,5	57	4,3	86	5,2	114	6,2
3	63	5	94	6,1	125	7,2
3,5	68	6	102	7,3	135	8,5
4	75	6,8	112	8,1	147	9,6
4,5	*		119	9,1	159	10,9
5					167	12,5
6	· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·		183	15,2







TFE Nozzle

Jets







Fog Nozzle is a nozzle that generates a total dispersion of water producing fog in seconds.

This revolutionary nozzle provides a pleasant feeling of freshness and humidification in the atmosphere.

They are entirely made of AISI 316 stainless steel, which provides high sturdiness and oxidation resistance, and provides a stylish finish to the fountain.

NOZZLE	FOG WIDE	FOG WIDE NOZZLE		
Code	666	97	Cod	
Inlet	G 1/4	G 1/4" M		
Jet diameter	Ø 1,4	Ø 1,4 mm		
Dimensions	38×14	mm	Dime	
Jet angle α [°]	l/min	m	Jet c	
68	0,72	4		
76	0,95	7		
84	1,4	15		
90	1,6	20		
95	2	30		
98	2,3	40		
102	2,8	60		

NOZZLE	FOG NARROV	V NOZZLE	
Code	70668		
Inlet	G 1/4"	М	
Jet diameter	Ø 1,4 mm		
Dimensions	26×14 mm		
Jet angle α [°]	l/min	m	
10	5,3	14	
15	7,6	28	
19	10,6	55	
23	17	138	

NICHE	FOG NICHE	
Code	70669	
Inlet	G 1/4" / 1"	
Drain	G 2"	
Dimensions	253×220×220 mm	
Material	Stainless steel AISI316	

FOG WIDE NOZZLE Code: 66697















JETS VULCANO S NOZZLE



Volcano nozzle produces a set of parabolic jets reaching different heights and leghts, achieveing a nice and visible water effect.

They are entirely made of AISI 316 stainless steel, which provides high sturdiness and oxidation resistance, and provides a stylish finish at the fountain.

VULCANO S NOZZLE Code: 67204		
Inlet	G 1" I	М
Jet diameter	Ø 1×6 mm +	20×3 mm
Dimensions	80 × 70	mm
Jet height [m]	l/min	m
0.5 m	27	1,3
1.0 m	35	2,3
1.5 m	43	3,1
2.0 m	49	3,7
2.5 m	55	4,4
3.0 m	60	5,2
4.0 m	72	6,6

* Product Upon Request

PROJECT VIEW



VULCANO S NOZZLE



Mushroom nozzle produces a perfectly laminar and semi-spherical transparent lamina. When falling it creates a completely continuous bell-shaped effect.

They are entirely made of AISI 316 stainless steel, which provides high sturdiness and oxidation resistance, and provides a stylish finish at the fountain.

MUSHROOM NOZZLE Code: 672	06		
Inlet	G 1	" F	
Dimensions AxB	300×80 mm		
Diameter [mm]	l/min	m	
250	29	1,2	
500	32	1,3	
750	40	1,4	
1000	50	1,5	

jets MUSHROOM NOZZLE



MUSHROOM NOZZLE









PROJECT VIEW



ACCESSORIES

NOZZLES	CODE
Jet Dancer Nozzle Short 16	67646
Jet Dancer Nozzle Long 16	67647
Jet Dancer Nozzle Short 20	67648
Jet Dancer Nozzle Long 20	67649

LIGHTING FIXATION	CODE
Fixation for Halospot light	67650

Rhythmic and elegant movements combined with the swing of the water provided by the Dancer jet contribute to create new sensations and dynamism just by the movement of the water.

The combination of light and water effects makes it innovative and spectacular, and without a doubt, it delivers the effects intended for the enjoyment of spectators.

The Dancer jet follows any kind of rhythm thanks to its axial movement.

The infinite number of sequences of this jet means that extremely spectacular shows can be put on.

DANCER JET Code: 67652		
Dimensions (L x W x H) [mm]	580 × 300 × 470	
Light type (optional)	RGB - DMX	
Dancer Jet nominal voltage [V]	230 VAC	
Power (Dancer) [W]	200	
Power rating [A]	1,1	
Water Inlet connection	1-1/2" G	
Jet diameter [mm]	16 / 20 (optional)	
Maximum water depth [mm]	500	
Jet movement range [°]	-60 / 60	
Jet movement velocity [°/s]	0 - 240	
Material	Stainless steel 316	
Weight [kg]	24	
Dynamic jet height	With individually pump and frequency inverter	
Protection class	IP 68	

DANCER JET



The Swing Dancer jet effect provides a show of light, color and graceful movements that express feelings and emotions transmitted through the magical combination of water and light, all of which creates the impression of a ballet staged on the water.

The multidirectional spout generates unique movements that create numerous shapes and figures. The jet can be programmed to go faster or slower so that it appears to dance on the water in dynamic, elegant movements.

1000

SWING DANCER JET Code: 67645 Dimensions (L x W x H) [mm]

Dimensions (L x W x HJ [mm]	1030 × 620 × 450		
Light type (optional)	RGB - DMX		
Dancer Jet nominal voltage [V]	230 VAC		
Power (Dancer) [W]	350		
Power rating[A]	1,9		
Water Inlet connection	2" G		
Jet diameter [mm]	16 / 20 (optional)		
Maximum water depth [mm]	500		
Jet movement range X axis [°]	-60 / 60		
Jet movement range Y axis [°]	-60 / 60		
Jet movement velocity in axis X[°/s]	0 – 120		
Jet movement velocity in axis Y[°/s]	0 – 240		
Material	AISI 316 stainlees steel		
Weight [kg]	55		
Dynamic jet height	With standal pump and frequency inverter		
Protecction level	IP 68		

JETS Swing dancer jet



PROJECT VIEW .

SWING DANCER JET







ACCESSORIES

NOZZLES	CODE
Jet Dancer Nozzle Short 16	67646
Jet Dancer Nozzle Long 16	67647
Jet Dancer Nozzle Short 20	67648
Jet Dancer Nozzle Long 20	67649

ASTRALPOOL

LIGHTING FIXATION	CODE
Fixation for Halospot light	67650

JETS DANCER NOZZLE

Dancer Nozzle is an ideal nozzle to combine with Dancer Jet and Swing Dancer Jet equipment. Its versatility in the lengths of thread allows to adapt to different types of lighting.

They are entirely made of nickeled brass and AISI 316 stainless steel, which provides high sturdiness and oxidation resistance, and provides a stylish finish to the fountain.

NOZZLE	DANCER NO			OZZLE LONG 16	DANCER NO		DANCER NC 2	
Code	676			647	676		676	
Inlet	G 1-1/	/2" M	G 1-	1/2" M	G 1-1/	′2" M	G 1-1,	/2" M
Jet diameter A	Ø 16	mm	Ø 10	6 mm	Ø 20	mm	Ø 20	mm
Recommend light	Halo (10403MIR) 10403W	NDMXI52/	(I1261MW	ılar led NDMXI52/ NDMXI52)	Halo (I0403MIR I0403W	NDMXI52/	Circul (11261MW1 11255MW1	NDMXI52/
JET HEIGHT [m]	l/min	m	l/min	m	l/min	m	l/min	m
0,5	46	1	46	1	70	1,2	70	1,2
0,75	55	1,3	55	1,3	80	1,3	80	1,3
1	62	1,5	62	1,5	87	1,5	87	1,5
1,25	70	1,9	70	1,9	95	1,8	95	1,8
1,5	76	2,1	76	2,1	104	2,1	104	2,1
1,75	82	2,4	82	2,4	111	2,4	111	2,4
2	88	2,6	88	2,6	119	2,7	119	2,7
2,5	99	3,2	99	3,2	135	3,3	135	3,3
3	108	3,7	108	3,7	148	4	148	4
3,5	117	4,5	117	4,5	160	4,6	160	4,6
4	125	5,1	125	5,1	171	5,2	171	5,2
5	138	6	138	6	197	6,4	197	6,4
6	150	7,5	150	7,5	217	7,6	217	7,6
7	164	8,5	164	8,5	238	8,9	238	8,9
8	176	9,6	176	9,6	257	10,2	257	10,2
9	187	11,2	187	11,2	274	11,3	274	11,3
10	198	12,5	198	12,5	290	12,6	290	12,6
11	208	13,8	208	13,8	306	13,9	306	13,9
12	216	14,6	216	14,6	322	15,1	322	15,1
14					348	17,6	348	17,6





DANCER NOZZLE LONG Code: 67647 - 67649





Dancer Nozzle

Jets

* Product Upon Request





JETS GLASSY JET WITH JUMPING EFFECT

Crystalline laminar nozzle that does not spill a single drop of water. From start to finish, a perfect parabolic path is followed that is created on the basis of the laws of fluid dynamics.

The Glassy jet shines light in the water as it follows its path. It only illuminates the water and does not cause any light pollution.

There is also the Jumping effect option, which throws small streams of water across the parabolic path.

GLASSY JET WITH JUMPING JET	JET S WITH JUMPING EFFECT	GLASSY JET L WITH JUMPING EFFECT
Code	66560	66562
Dimensions (L x W x H) [mm]	300 × 220 × 450	440 × 320 × 710
Light type	RGB - DMX	RGB - DMX
Light nominal voltage [V]	24 VDC	24 VDC
Jumping nominal voltage [V]	24 VDC	24 VDC
Power (Jumping) [W]	24	24
Power (Light) [W]	ц	4
Power (Total) [W]	28	28
Water inlet connection	1" G	1" G
Jet diameter [mm]	12 standard	16 standard
Maximum water depth [mm]	315	480
Jet rake range [°]	30-90	30-90
Light control	DMX (3 channel)	DMX (3 channel)
Jumping system control	Relay	Relay
Material	Stainless steel 316	Stainless steel 316
Weight [kg]	12	26
Dynamic parabola	With individually pump and frequency inverter	With individually pump and frequency inverter
Maximum parabola of water	ц	6
Flow (max. parabola) [m3/h]	2	4,2
Pressure (max. parabola) [bar]	0,4	0,6
Hydrualic operation	130 microns filtered water	130 microns filtered water

GLASSY JET S WITH JUMPING EFFECT Code: 66560



GLASSY JET L WITH JUMPING EFFECT Code: 66562









Glassy Jet with Jumping Effect

Jets





JETS **GLASSY** JET

Crystalline laminar nozzle that does not spill a single drop of water. From start to finish, a perfect parabolic path is followed that is created on the basis of the laws of fluid dynamics.

The Glassy jet shines light in the water as it follows its path. It only illuminates the water and does not cause any light pollution.

There is also the Jumping effect option, which throws small streams of water across the parabolic path.

GLASSY JET	GLASSY JET S	GLASSY JET L	GLASSY JET S Code: 66559
Code	66559	66561	234
Dimensions (L x W x H) [mm]	270 × 220 × 380	390 × 320 × 560	
Light type	RGB - DMX	RGB - DMX	(m) 25
Light nominal voltage [V]	24 VDC	24 VDC	
Jumping nominal voltage [V]	-	-	
Power (Jumping) [W]	-	-	306
Power (Light) [W]	4	ц	R.INT. 1"W. BSP.
Power (Total) [W]	4,5	4,5	0.5
Water inlet connection	1" G	1" G	
Jet diameter [mm]	12 standard	16 standard	0 0.5 1 1
Maximum water depth [mm]	320	480	
Jet rake range [°]	30-90	30-90	
Light control	DMX (3 channel)	DMX (3 channel)	
Jumping control system	Relay	Relay	GLASSY JET L Code: 66561
Material	ASIS 316 stainless steel	ASIS 316 stainless steel	336
Weight [kg]	7	20,5	
Dynamic parabola	With individually pump and frequency inverter	With individually pump and frequency inverter	
Maximum parabola of water	4	6	
Flow (max. parabola) [m3/h]	2	4,2	
Pressure (max. parabola) [bar]	0,4	0,6	R. INT.
Hydrualic operation	130 microns filtered water	130 microns filtered water	1" W. BSP.







4.5 (=)





Jets





JETS GLASSY JET WITHOUT LIGHT

Crystalline laminar nozzle that does not spill a single drop of water. From start to finish, a perfect parabolic path is followed that is created on the basis of the laws of fluid dynamics.

There is also the Jumping effect option, which throws small streams of water across the parabolic path.

GLASSY JET WITHOUT LIGHT	GLASSY JET S WITHOUT LIGHT	GLASSY JET L WITHOUT LIGHT
Code	67306	67307
Dimensions (L x W x H) [mm]	270 × 220 × 380	390 × 320 × 560
Light type	-	-
Light nominal voltage [V]	-	-
Jumping nominal voltage [V]	-	-
Power (Jumping) [W]	-	-
Power (Light) [W]	-	-
Power (Total) [W]	-	-
Water inlet connection	1" G	1" G
Jet diameter [mm]	12 standard	16 standard
Maximum water depth [mm]	320	480
Jet rake range [°]	30-90	30-90
Light control	-	-
Jumping control system	-	-
Material	ASIS 316 stainless steel	ASIS 316 stainless steel
Weight [kg]	6,5	20
Dynamic parabola	With individually pump and frequency inverter	With individually pump and frequency inverter
Maximum parabola of water	4	6
Flow (max. parabola) [m3/h]	2	4,2
Pressure (max. parabola) [bar]	0,4	0,6
Hydrualic operation	130 microns filtered water	130 microns filtered water

GLASSY JET S WITHOUT LIGHT Code: 67306



GLASSY JET L WITHOUT LIGHT Code: 67307









Glassy Jet Without Light

Jets

* Product Upon Request







The Rocket jet gives the effect of an explosion of water from the ground that rises up in a split second to above the height of really tall buildings as it can reach heights of up to 50 meters.

The explosion of water creates a perfect vertical line that will be the centre of attention anywhere.

The lighting highlights the height of the water to turn it into a powerful beam of light, which rises at high speeds and draws coloured lines on the water.

The combination of several units of this effect will create spectacular high speed sequences.

ROCKET JET	ROCKET JET S	ROCKET JET M	ROCKET JET L
Code	66564	66565	66566
Dimensions (L x W x H) [mm]	3 × 248 × 727	530 × 515 × 887	642 × 514 × 1558
Nominal voltage [V]	24 VDC	24 VDC	24 VDC
Power [W]	25	2 × 25	2 × 25
Power rating [A]	1,1	2 × 1,1	2 × 1,1
Air Inlet connection	1" G	2 × 1" G	2 × 1" G
Air pressure [bar]	2,5	5	10
Water level [mm]	620	720	1320
Jet diameter [mm]	19	19	19
Jet height [m]	15	30	50
Material	Stainless steel 316	Stainless steel 316	Stainless steel 316
Weight [kg]	18	58	75
Refill time (s)	5	15	30
Air consumption (L)	15	120	225

ROCKET JET S Code: 66564



ROCKET JET M Code: 66565



ROCKET JET L Code: 66566





Rocket Jet





JETS Rocket Horizontal Jet



PROJECT VIEW





The Rocket jet gives the effect of an explosion of water from the ground that rises up in a split second to above the height of really tall buildings as it can reach heights of up to 50 meters.

The explosion of water creates a perfect vertical line that will be the centre of attention anywhere.

The lighting highlights the height of the water to turn it into a powerful beam of light, which rises at high speeds and draws coloured lines on the water.

The combination of several units of this effect will create spectacular high speed sequences.

ROCKET HORIZONTAL JET	Code: 66563
Dimensions (L x W x H) [mm]	1350 × 305 × 630
Nominal voltage [V]	24 VDC
Power [W]	25
Power raring [A]	1,1
Air Inlet connection	1" G
Air pressure (max.) [bar]	4,5
Maximum water depth [mm]	570
Minimum water depth [mm]	470
Jet diameter [mm]	19
Jet height [m]	20
Material	AISI 316 stainless steel
Weight [kg]	31
Refill time (s)	10
Air consumption (L)	38

ROCKET HORIZONTAL JET


The stylised, tall and controlled Fire jet produces an eye-catching effect, not commonly seen, let alone in a fountain! Fire has always been an larger-than-life feature that emanates power and strength, and in a fountain display, it adds the cherry on the cake.

Water and fire, two opposite elements that marry perfectly when a magic show is put on; an explosive combination and the most impressive you could ever imagine.

The hard work done has led to a new concept: a variety of colours for the fire jets: blue, yellow, green, ...

The flames do not smell or produce smoke because the system does not run on gas or fuel oil. The fluid that creates smokeless flames is readily available everywhere.

FIRE JET Code: 66567	
Dimensions (L x W x H) [mm]	250 × 250 × 553
Nominal voltage [V]	230 VAC
Power [W]	500
Power rating [A]	2,7
Inlet connection	1/4" G
Pressure (max.) [bar]	16
Maximum water depth [mm]	315
Jet height [m]	4 - 10
Material	Stainless steel 316
Weight [kg]	14,5
Protection rating	IP 68













JETS SWITCH S SYSTEM

Switch System is a dynamic jet ideal for interactive fountains such as Funsquare type, to produce fast water games with individual control for each installed jet.

The design of this jet allows state changes without water hammer in the installation.

It has many tile models being able to choose between different types of round and square designs.

SWITCH S SYSTEM			
Dimensions [mm] (see drawings)	300 × 300 × 371 / D.400 × 371		
Nominal Voltage [V]	24 V	'DC	
Power (without LED) [W]	2!	5	
EV Nominal Current [A]	1,	1	
Lighting Control	DN	ſΧ	
Water connections	1"	G	
Jet diameter [mm]	12	<u>2</u>	
Material	Stainless steel 316 / Brass		
Protection class	IP 68		
Hydraulic requirements	130 microns filtered water		
JET HEIGHT [m]	l/min	m	
0,5	25,4	4,5	
0,75	30,2	4,8	
1	33,6	5,0	
1,25	39,0	5,5	
1,5	40,9	5,6	
1,75	45,8	6,1	
2	46,6	6,2	
2,5	51,9	6,7	
3	57,2	7,3	
3,5	62,9	8,0	
4	66,4	8,5	





Switch S _{Jets}





JETS SWITCH L SYSTEM



PROJECT VIEW





Switch System is a dynamic jet ideal for interactive fountains such as Funsquare type, to produce fast water games with individual control for each installed jet. The design of this jet allows state changes without water hammer in the installation.

For dry fountains there is the option of the Switch System with 316 stainless steel niche and integrated led RGB-DMX projectors.

SWITCH L SYSTEM Code: 66570 (Niche not included)			
Dimensions (LxWxH) [mm]	210 × 120 × 261		
Nominal Voltage [V]	24 VDC		
Power [W]	25		
Nomial Current [A]	1,1		
Water connections	1-1/2" G		
Maximum flow [I/min]	290		
Maximum pressure [bar]	4		
Pressure drop Qn [bar]	0,4 – 1		
Material	Stainless steel 316 / Brass		
Weight [kg]	6,5		
Protection class	IP 68		
Hydraulic requirements	130 microns filtered water		

SWITCH L NICHE Code: 66572	
Dimensions (L x W x H) [mm]	450 × 435 × 500
Material	Stainless steel 316
Weight [kg]	19
Water connections	1 × 1-1/2", 1 × 2"
Connections for wiring	2 × 1"

SWITCH L SYSTEM Code: 66570 SWITCH L NICHE Code: 66572







Cosmos produces a sequence of perfect spherical water droplets that float in the air and shoots the water up and down. These movements emulate cosmic water particles that act randomly.

The illumination emphasises the effect by producing a random display of different coloured particles.

Cosmos can alternate the droplets with another astonishing effect: small, extremely fast vertical jets able to create high-speed cascades, waves, etc.

COSMOS Code: 66553	
Dimensions (L x W x H) [mm]	144 × 80 × 259
Light type	RGB - DMX
Light nominal voltage [V]	24 VDC
Cosmos nominal voltage [V]	24 VDC
Power (Light) [W]	3
Power (Cosmos) [W]	14
Power (Total) [W]	17
Power rating[A]	0,6
Waterinlet connection	3/8" G
Jet diameter [mm]	ц
Jet function flow h=1m [l/min]	3,4
Pressure (max.) [bar]	1,5
Light control	DMX (3 channels)
Material	AISI 316 stainless steel / Brass / Other
Weight [kg]	2
Protection rating	IP 68













The InMotion system draws on the very latest technology for controlling water features. Users will now be able to operate fountain displays by using their body signals and gestures. When users move their arms up or down, the jets go faster or slower.

This system works with the Funsquare fountains and any fountain with Swing Dancer or Dancer jets.

INMOTION SYSTEM Code: 66573	3
Detection range [m]	5 – 10 m
Connection	Ethernet
Recognized gestures	Dynamic gestures Static gestures



The interactive sensors are the perfect complement to be placed in any ornamental fountain.

Each sensor can produce a different variability into the fountain actuation in real time, producing a guaranteed fun for the whole family.

INTERACTIVE SENSOR BUTTONS	
Code	66574 (black) / 66574CL02 (blue) / 66574CL03 (green) / 66574CL04 (red)
Dimensions (L x W x H) [mm]	250× 255 × 258
Nominal Voltage [V]	24 (VDC)
Output	Digital Output (24 VDC)
Inlet Connection	1"
Material	Stainless steel 316 - PE-HD -500
Weight [kg]	7,8

INTERACTION ASTRALPOOL



* Product Upon Request

INTERACTIVE SENSOR BUTTONS







The coding which appears in more detail later refers to the lamps and projectors OnLED

Α	Colour of LED emission	В	Material of the trim	DMX	Projectors for DMX system
С	Shape of face plate	D	Optic type		



Example: I0102MPRI52

STD projector for a concrete pool, multicolour, round plastic face plate, without optic.

10306WPRNI52

Mini projector with quick couplingi, white, round plastic face plate, narrow type optic.

Important: Always to include I52 at the end of the code

IDENTIFICATION

Product recommended for:



Underwater and outdoor installations



IP

<u>First figure</u>

Level of protection against the ingress of solid objects

- 0 No protection
- 1 Protection from solid objects with a diameter greater than 50mm
- 2 Protection from solid objects with a diameter greater than 12.5 mm
- 3 Protection from solid objects with a diameter greater than 2.5 mm
- 4 Protection from solid objects with a diameter greater than 1 mm
- 5 Protected from dust
- 6 Hermetic to dust

Second figure

Level of protection against ingress of water

- 0 No protection
- 1 Dripping water
- 2 Dripping water when tilted up to 150
- 3 Spraying water
- 4 Splashing water
- 5 Water jets
- 6 Powerful water jets
- 7 Protected from immersion effects
- 8 Protection from prolonged immersion

Class

 $\langle ||| \rangle$

(_____) Class I Luminaire in which the protection against electric shocks depends on the main insulation and an additional safety measure: earthing.

Class II Luminaire in which the protection against electric shocks depends on the main insulation and an additional safety measure: double or reinforced insulation.

Class III Luminaire in which the protection against electric shocks depends on feeding it with a low voltage power supply.

CE Marking

ILLUMINATION NIQ PROJECTOR

The NIQ is used for spas, wellness centres, stairs. It has the same function as the Mini projector but with smaller dimensions.

CODE	LIGHT	FACE PLATE	OPTIC	OPTION	ASTRALPOOL
11245	W Cool white	Material	N Narrow	DMX	152
11246	WW Warm white	P Plastic	M Medium		
	M Multicolour	I Stainless Steel	W Wide		
11287	MDMX Multicolour DMX				
		Shape			
		S Square			
		R Round			

Consumption

Monocolour: 4W (6VA) Multicolour: 4W (7VA) MDMX: 4W (4VA)

Voltage

Monocolour: 12 Vac Multicolour: 12 Vac MDMX: 24 Vdc

Lumens

Monocolour: 315 lm Multicolour: 186 lm MDMX: 186 lm

Efficiency

Monocolour: 78,7 lm/W Multicolour: 46,5 lm/W MDMX: 46.5 lm/W

Life Span

L80 - 60.000h

Protection level









NIQ Monocolour/ monocolor Optic N



📮 }i

an langanan da ana proy na an langanan dan ana proy Na projekti anga ana k

NIQ





0.08

100

3N

Multicolour/ multicolor Optic W



CONTROL

Multicolour

power supply

DMX

10826152 Modulator

10831152 Push-button

10828152 Remote control

IO832DMXI52 DMX power supply

10832DMXFEI52 DMX external



800





11246 FITTED NIQ ADJUSTABLE PROJECTOR









Niq Recessed Projector

Fitted Niq Adjustable

Illumination



ILLUMINATION NANO PROJECTOR

Despite its small dimensions, this wall fitting has considerable light output. Ideal for lighting jets up to 2 meters high in ornamental fountains or it can be used underwater indoors and outdoors where small dimensions are required.

Made of AISI 316 stainless steel with protection degree IP68.

Consumption

Monocolour: 3W (4VA) Multicolour: 3W (4VA) MDMX: 3W (3VA)

Voltage

Monocolour: 12 Vac Multicolour: 12 Vac

MDMX: 24 Vdc

Lumens

Monocolour: 250 lm Multicolour: 150 lm

MDMX: 150 lm

Efficiency

Monocolour: 83,3 lm/W Multicolour: 50 lm/W

MDMX: 50 Im/W

Life Span

L80 - 50.000h

Protection level

^{IP68} ()) € €



11234

1239



NANO PROJECTOR WITH JOINTS

83

NANO PROJECTOR Ø40





Nano Projector Ø40

Illumination



NEW PRODUCT MINI / MINI + PROJECT

The MINI projector is the best option to illuminate ornamental fountains, small swimming pools and spas. Only 3 Leds are used, but due to its high level of lighting, it reaches similar levels to traditional lamps. It can be installed indiscriminately submerged or outside the water.

Possibility of intensive, intermediate or extensive lens.

MINI Projector Quick Couplin is the best choice for lighting corners, small pools and spas.

Directional Projector MINI is especially designed for fountains, gardens and decorative aquatic installations. It is supplied with screws and studs for fitting.

MINI Recessed Projector is conceived for installing on fountains and water spaces. Its glass lens and AISI 316 stainless steel trim are designed to 500 Kar. static force.

CODE	LIGHT	FACE PLATE	OPTIC	OPTION	ASTRALPOOL	
10306	W Cool white	Material	N Narrow	DMX	152	
10307	WW Warm white	P Plastic	M Medium			I
10321	M Multicolour	I Stainless Steel	W Wide			1
10322	MDMX Multicolour DMX					I
10406	MWDMX Multicolour White DMX	Shape				I
10411		S Square				1
11226		R Round				5
11282						
11285						

11282 11285 11286	
	10307 MINI PROJECTOR FOR SPAS 10322 MINI+ PROJECTOR FOR SPAS

73





Consumption	Mini	Mini +	
Monocolour:	4W (6VA)	6W (9VA)	
Multicolour:	4W (7VA)	6W (6VA)	
MDMX:	4W (4VA)	6W (6VA)	
MWDMX:	5W (5VA)	8W (8VA)	
Voltage			
Monocolour:	12 Vac	12 Vac	
Multicolour:	12 Vac	12 Vac	
MDMX:	24 Vdc	24 Vdc	
MWDMX:	24 Vdc	24 Vdc	
Lumens			
Monocolour:	315 lm	550 lm	
Multicolour:	186 lm	250 lm	
MDMX:	186 lm	250 lm	
MWDMX:	300 lm	430 lm	
Efficiency			
Monocolour:	78,7 lm/W	91,66 lm/W	
Multicolour:	46,5 lm/W	55 lm/W	
MDMX:	46,5 lm/W	55 lm/W	
MWDMX:	60 lm/W	53,75 lm/W	
Life Span			
L80 - 50.000h			
Protection level			
IP68		•	
ώζε			





226 MINI RECESSED PROJECTOR 11285 MINI RECESSED PROJECTOR SS 11282 MINI+ RECESSED PROJECTOR 1286 MINI+ RECESSED PROJECTOR SS



M6 Din 799

ASTRALPOOL



Mini Projector Quick Couplin / Mini +



Directional Projector Mini / Mini +

Illumination



Mini Recessed Projector

/ Mini +

Illumination

Illumination



III UMINATION MINI / MINI + PROJECT R









15

22















Flux/ Flujo 300 lm







Flux/ Flujo 186 lm

























🚆 }:



MINI + MWDM	IX/ MWDMX Optic N		
	0-05 Beard7-67		
. 818		Man	Med
1.00		-	1072
7.00		1001	168
3.00		342	341
6.00		285	102
1.00	. 80	- 184	523





ILLUMINATION **CIRCULAR** Ø200

Projector designed for fitting directly to the jets of ornamental fountains, thus ensuring that they are properly illuminated and emit an even source of light. Has a stainless steel finish.

Possibility of intensive, intermediate or extensive lens.



Monocolour: 16W MWDMX/: 16W

Voltage

24Vdc

Lumens



Circular Ø200 1" 1/2 THREAD

Illumination



ILLUMINATION **CIRCULAR** Ø300

A large projector with high luminous performance for fitting directly to the jets of ornamental fountains of up to 11/2". Made of stainless steel.

CODE	LIGHT	OPTIC	OPTION	ASTRALPOOL
11255	W Cool white WW Warm white (Upon Request) MWDMX Multicolour White DMX	N Narrow M Medium W Wide	DMX	152

IGHT	OPTIC	OPTION	ASTRALPOOL	
✓ Cool white ☞ Warm white (Upon Request) ₩DMX Multicolour White DMX	N Narrow M Medium W Wide	DMX	152	

Max Mod

002105854

0305714538

9901 6263

6511 3554

3628 2262

CONTROL 10828152 Remote control

10826152 Modulator 10831152 Push-button **I0832DMXI52** DMX power supply I0832DMXFEI52 DMX external power supply

Consumption

Monocolour: 80W MWDMX: 80W

Voltage

24Vdc

Lumens

Monocolour: 7.200 lm MWDMX: 4,100 lm

Efficiency

Monocolour: 90 lm/W MWDMX: 51 lm/W

Colour

16.000.000

Life Span

L80 - 50.000h

Protection level

IP68 (i)) (€

CIRCULAR Ø300 11255









Flux/ Flujo 7.200 lm

Circular Ø300

11

1.00

2.00

100-

4.00

5.00



Circular Ø300

Illumination





ILLUMINATION HALOSPOT PROJECTOR

High-resistance projector, made with stainless steel. It is ideal for ornamental fountains an watter jets. It should be installed completely submerged in water. It is provided with screws and studs for fitting. Possibility of intensive, intermediate or extensive lens.

CODE	LIGHT	FACE PLATE	OPTIC	OPTION	ASTRALPOOL	Multicolour: 22W (31VA) MWDMX: 30W (30VA)
101-00	W Cool white	Mantautau	N. Marine	DMY	152	Voltage
I0403 W Cool white WW Warm white (Upon Request) M Multicolour MWDMX Multicolour White DMX		Material P Plastic I Stainless Steel	N Narrow M Medium W Wide	DMX		Monocolour: 12 Vac Multicolour: 12 Vac MWDMX: 24 Vdc
		Shape				Lumens
		S Square R Round				Monocolour: 1.450 lm Multicolour: 1.100 lm MWDMX: 1.750 lm
						Efficiency
CONTROL	IO403 HAL	OSPOT PROJECTOR				Monocolour: 91 lm/W Multicolour: 50 lm/W MWDMX: 58,33 lm/W
10828152 Remote	<		Ø108			Life Span
10826152 Modula 10831152 Push-bu			\times			L80 - 50.000h
10832DMXI52 DM	1X power supply	6				Protection level
I0832DMXFEI52 D power supply	MX external	Ø165				^{IP68} ⊕€€

Consumption

Monocolour: 16W (23VA)



Halospot Projector

Illumination





III UMINATION HALOSPOT PROJECT





























Flux/ Flujo 1100 lm

ASTRALPOOL 🖍





ILLUMINATION **KIBELE** PROJECTOR

A large projector with high luminous performance. Made of stainless steel. Ideal for installation in ornamental fountains with jets with high flow rates. Possibility of intensive, intermediate or extensive lens.

Ø170,5

Ø182

It is supplied with screws and wall plugs.

CODE LIGHT FACE PLATE OPTIC OPTION ASTRALPOOL 10407 W Cool white Material N Narrow DMX 152 WW Warm white (Upon Request) M Medium P Plastic M Multicolour I Stainless Steel W Wide **MWDMX** Multicolour White DMX MW Multicolour Shape M+W S Square R Round

CONTROL

I0828I52 Remote control I0826I52 Modulator I0831I52 Push-button I0832DMXI52 DMX power supply I0832DMXFEI52 DMX external power supply

Consumption

Monocolour: 58W (60VA) Multicolour: 48W (64VA) MWDMX: 60W (60VA)

Voltage

Monocolour: 12 Vac Multicolour: 12 Vac MWDMX: 24 Vdc

Lumens

Monocolour: 4.320 lm Multicolour: 2.544 lm MWDMX: 3.100 lm

Efficiency

Monocolour: 74,4 lm/W Multicolour: 53 lm/W MWDMX: 56 lm/W

Life Span

L80 - 50.000h

Protection level

IP68 ()→ C€

×



KIBELE PROJECTOR

10407



Kibele Projector

Illumination





ILLUMINATION **KIBELE** PROJECTOR































ASTRALPOOL





NEW DESIGN ILLUMINATION **LINEAR ESCALA** PROJECTOR

Strip LED projector featuring an AISI 316 stainless steel profile.

A multipurpose light that may be combined, installed and used in many different ways. Highly versatile, it is an ideal decorative light for use outdoors and in water features. Includes fastening supports.

W: 1m. 500lm - 0,5m. 250lm MWDMX: 1m. 640lm - 0,5m. 320lm CODE LIGHT LENGTH OUTPUT OPTION ASTRALPOOL CONTROL Efficiency 11320 w Cool white **05** 0.50m DMX 152 T1output Monocolour W: 1m. 42lm/W - 0,5m. 40lm/W **NW** Neutral white 10 1m 0 2 outputs 10847152 Power supply MWDMX: 1m, 40lm/W - 0.5m, 40lm/W A Amber **MWDMX** Multicolour DMX Colour 10832DMXI52 DMX-MW Power supply White DMX L80 - 60.000h MW Multicolour M+W 10832DMXFEI52 DMX Ext. power supply **Protection level**





ESCALA (1 m) Monocolour/ monocolor







Man

100

ESCALA (0,5 m)

10

MWDMX/ MWDMX







I1320MW050

Consumption

Voltage 24 Vdc Lumens

IP68 (€)

W: 1m. 12W - 0.5mm 6W

MWDMX: 1m. 16W - 0,5m. 8W





208

Flux/ Flujo 250 lm



PROJECT VIEW



Adjustable 13 W linear and the first sector of the sector

Adjustable 13 W linear projector for both indoor and outdoor areas. Made from aluminum and white DMX, this multicolour projector is perfect for wall washing.

CODE	LIGHT	FACE PLATE	OPTION	ASTRALPOOL
11279	W Cool white WW Warm white MWDMX Multicolour White DMX	Material P Plastic I Stainless Steel	N Narrow M Medium W Wide	152
		Shape S Square R Round Om		

CONTRO	L

Multicolour 10826 Modulator 10828 Remote control 10831 Push-button DMX 10832DMX DMX power supply 10832DMXFE DMX external power supply

Consumption															
MWDMX: 13W	• • •		•••		 					•		 		 	•
Voltage															
24 Vdc														 	
Lumens															
1.000lm															
Efficiency															
71,43 lm/W															
Life Span												 		 	
L80 - 60.000h															
Protection level												 		 	
IP65					_	1									
∞C€						>	K								
	• • •	• •	• •	• •	• •	• •		٠	• •	٠	• •		 *	 • •	



11279 LINEAR ADJUSTABLE PROJECTOR





Linear Adjustable Projector

Illumination



ILLUMINATION STARRY SKY EFFECT



The installation of STARRY SKY in pools clad with ceramic tiles—other than mosaic pieces—glass sheets or tiles, marble and other natural stones, is the most effective technique to display the magic of fiber optics underwater. Each Kit consists in 40 bright points (I1089) or 150 bright points (I1090) with excellence quality. The kit works in 12Vac powered fixtures don't have minimum-distance to water restrictions.

CODE	LIGHT
11089	W White WW Warm white
11090	W White WW Warm white M Multicolour

11089 STARRY SKY KIT 40 STRANDS



PROJECT VIEW







I1090 STARRY SKY KIT 150 STRANDS 6-14m



Family of small connectors ideal for connections if space is limited. With an IP68 rating of up to 2 bar and metal inserts for the connections.

Pole numbers	10892
4	4 pole connection (Kit 5 unities + 2 keys)
Cable with	(Kit o unities + 2 keys)
Max 2.5 mm ²	I0912 Air connector IP68 4 poles
Min-Max cable diameter	•
7.0 mm - 12.0 mm	I0913 Air connector IP68 4 poles
Maximum current	XDRY
16A	10914
Maximum voltage	Key for aerial connector
48V	10916
Working temperature	IP68 connector T3 poles
-40°C to +125°C	
Material	
PA66GF UL94 VO GWT 960°C	
Protection level	
IP68	
CE & RoHS	
••••••	

ILLUMINATION ASTRALPOOL



10892 4 POLE CONNECTION (KIT 5 UNITIES + 2 KEYS)



ILLUMINATION ONDMX CONTROL SYSTEM



Total control system of illumination by $\ensuremath{\mathsf{PC}}$ or through a programmable and autonomous module.

It is composed by the OnDMX module (USB-DMX interface) and an intuitive software, it grants to the user a total control of a projector or group of projectors.

It allows the colour choice among more than 16 million colours.

The system turns into the ideal solution for the practically indefinite creation of scenes of duration with spectacular results.

10834152 ONDMX CONTROLLER



System that complements the Total OnLED system, of the Modulator. With it you will be able to control the following actions:

- Switching the lamps on and off
- Changing colour
- Changing colour sequence
- Speed of colour sequence
- Switching off function (sleep)
- Synchronises water, light and sound.

10835152 ONDMX PRO CONTROLLER



ILLUMINATION ONDMX PRO CONTROL SYSTEM


This power pack can handle up to 9 projectors separately (27 DMX channels) or grouped together (3 DMX channels). It can be directly plugged into a 230 V AC power supply. Internal 60 W power adapter included.

10832DMXI52 DMX DRIVER ONLED POWER SUPPLY



ILLUMINATION ASTRALPOOL



The power supply can supply up to 9 projectors individually (27 DMX channels) or together (3 DMX channels). It is connected directly to 230V AC. External power supply required. Maximum Power 400 VA per unit.

10832DMXFEI52 DMX DRIVER ONLED EXTERNAL POWER SUPPLY



ILLUMINATION DMX DRIVER EXTERNAL POWER SUPPLY



ILLUMINATION ONLED MODULATOR



Total OnLED System, with which the switching on and off of the lamp can be controlled, changes colour and programme and timers to switch off.

10826152ONLED MODULATOR10827152ONLED MODULATOR 1-110V



System that complements the Total OnLED system, of the Modulator. With it you will be able to control the following actions:

- Switching the lamps on and off
- Changing colour
- Changing colour sequence
- Speed of colour sequence
- Switching off function (sleep)

10828152 ONLED REMOTE CONTROL



ILLUMINATION ONLED REMOTE CONTROL



The OnLED WiFi Access Point installed next to the modulator enables broadband connections to be made with smartphone and tablet devices.

By downloading the OnLED App onto your smartphone or tablet (using an Android or iOS system), you will be able to control your OnLED lamps and projectors.

10876152ONLED WIFI ACCESS POINT10877152ONLED MODULATOR + ONLED WIFI ACCESS POINT 230V10878152ONLED MODULATOR + ONLED WIFI ACCESS POINT 120V



ILLUMINATION ASTRALPOOL



Application for controlling any OnLED lamp or projector from smartphones/tablets using an Android or iOS system (iPhone/iPad).

By free downloading the OnLED onto your smartphone or tablet, you will be able to change the colours, sequences, speed, and time you wish to switch off your OnLED lamps and projectors. ILLUMINATION ONLED APP

Avaible on:











ILLUMINATION POWER SUPPLY



Power supply by LED tecnhology products, especially designed for use in aquatic installations liks pools or fountains.

 I0898
 Power supply 24VDC 120W

 I0899
 Power supply 24VDC 240W

 I0847
 Power supply 24VDC 480W

 I0908
 Power supply 24VDC 960W

ILLUMINATION SAFETY TRANSFORMERS



Single-phase Safety Transformers, especially designed for use in aquatic installations like pools or fountains.

With the protection degree IP20 or more, primary of 230V AC and secondary of 12-13-14V AC.

10820 Safety transformer IP20 350 VA

- 10821 Safety transformer IP20 130 VA
- 10822 Safety transformer IP65 350 VA
- 10823 Safety transformer IP20 700 VA

BASIC ONLED

Electric diagram that is obtained through a Pushbutton (n/c) + Safety transformer. The size of the transformer depends on the number of spotlights that are installed and their consumption. For example, if it has to power 5 24W spotlights, the transformer should be 125W. An input of 12V AC must reach the lamp. With every click, it changes colour or program, offers a range of 7 colours, as well as 7 colour changing programs.

TOTAL ONLED

El Outline based on the OnLED Modulator, for increasing the number of colours and sequences of the spotlights. With it, it is possible to turn the spotlight on and off, change 12 colours and 8 sequences and control the speed of the sequences and the power off timer. The Modulator also has an antennae with that can reach up to 50m. with which it can be synchronized with the OnLED Remote Control (10828152). The Modulator should be installed before the safety transformer and is connected to VAC through two terminals indicated as RED and is connected to the transformer primary through two terminals indicated with TRF. It is recommended to install the Modulator ensuring it is protected from corrosive environments.

ON DMX

Those that want total control of the lighting can use the spotlights with DMX adaptation and OnDMX Control, and then they can independently control all the spotlights, and obtain more than 16.000.000 colours and infinite sequences. Each driver handles 27 DMX channels.



ILLUMINATION V:NANO





Made even for the roughest environments, the V:Nano represents Syncronorm's smart solution for smaller and more intimate fountain show installations. The V:Nano 512 or 1024 "music" show controller is a DIN-rail fan-less & ruggedized embedded system with a highly efficient low power CPU chipset.

The V:Nano can withstands wider temperature ranges while featuring DMX 512/1990 ports, an isolated Ethernet port with 10/100 Mbit, a micro SD card slot and a 2×16 LCD segment-display.

A perfect match for smaller stand-alone fountains as well as musical fountain installations, both feature 8×digital I/O's.

The V:Nano is fully compatible with our fountain control system Depence. Easily enhance your workflow by uploading shows via SD card or your local network.

Key Features:

- DIN-Rail Mounting
- Scheduler
- Full RDM Support
- Sensor Connectivity
- Remote Control
- V:Nano Scripting
- SD-Card Memory
- Music Playback

V:NANO	72255 V:Nano 512	72256 V:Nano 1024 Music		
Dimensions	160×90×85 mm DIN Rail			
Weight	0.33 kg			
Protection Class	IP	20		
Power Supply	1524V I	DC / 8W		
Operation Temperature	040°/ 080% humidity			
Certification	CE			
Outputs	1× DMX-RDm 512ch	2× DMX-RDM 1024ch		
	-	3.5mm Audio		
	8× Digital Output (24V DC, max 1A)			
Inputs	8× Digital Input (max 30V DC)*			
Audio Playback	No	Yes		
Memory	microS	iD Card		

V:NANO



Next to Depence², our brand-new software system, we also have redesigned our top-level standalone show controller, the V:Server.

Alongside a new 19inch rack aluminium case it now features a touch screen interface on the front-panel next to a multicolor LED Logo.

The V:Sever3-Touch also comes with integrated optical isolated digital and analog I/Os to directly connect sensors and triggers.

The new node-based logic system of Depence² offers you maximum flexibility for any kind of interactive installation. Pre-existing Depence projects are still fully compatible as well.

The V:Server3-Touch will support projects created in former versions of Depence further on. With high performance and most stable connectivity, the V:Server still remains the perfect choice for running multimedia shows, while offering full ArtNet & RDM support as well as timecode features, and much more.

Key Features:

- BMI Logic Automation
- Scheduler
- Touch-optimized HMI/Live Panel
- Timecode I/O
- DMX-RDM Support
- ArtNET RDM Support
- Sensor Connectivity
- Remote Access
- Music Playback

V:SERVER3-TOUCH



ILLUMINATION NEW PRODUCT



V:SERVER3-TOUCH				
Dimensions	19" 3HE 330mm depth			
Weight	8.5kg			
Protection Class	IP 20			
Power Supply	110 / 230V @ 50Hz			
Operation Temperature	040° / 080% humidity			
Certification	CE			
Connectors	4× DMX RDM XML-5 Pin, 1× RJ45 Ethernet, 2× XLR 3-Pin Symmetric Audio, 1× DVI-Out, 1× SMPTE XLR 3-Pin, 1× RS232, 3× USB 2.0, 1× Emergency Stop, 8× Digital Input, 8× Digital Output, 12× Analog I/O			
Memory	120 GB solid state hard drive			

COMPLEMENTARY PRODUCTS **LEVEL** CONTROL SYSTEM

This control system provides a complete solution for controlling the water level in any fountain. This system makes it possible to fill a fountain automatically and acts as a security system for pumps if a fountain's water level drops too low.

The level control sensor is a very robust model that is resistant to oxidation and made entirely of AISI 316 stainless steel.

In the case of the Level Control Sensor Adjustable, the costumer receives the product with an standard and equal length on all rods, in order that the costumer adjusts this length according to the installation.

LEVEL CONTROL SENSOR Code: 66636

Dimensions (L x W x H) [mm]	101 × 55 × 177
Level range [mm]	1000
Difference between levels [mm]	20
Number of electrodes	5
Cable included	5 × 1 10 m
Material	AISI 316 stainless steel
Weight [kg]	2,3
Protection rating	IP 68

LEVEL CONTROL UNIT Code: 666	37
Dimensions (L x W x H) [mm]	53 × 66 × 92
Voltage [V]	230 VAC
Electrode inputs	5
Outputs	2 relay outpus up to 8A
Indicator led	1 power, 2 outputs
Material	Plastic housing
Mounting	DIN rail
Protection rating	IP20

LEVEL CONTROL SENSOR ADJUST	ABLE Code: 67444
Dimensions (L x W x H) [mm]	101 × 55 × 1046
Level range [mm]	1000
Difference between levels [mm]	20
Number of electrodes	5
Cable included	5 × 1 10 m
Material	AISI 316 stainless steel
Weight [kg]	2,6
Protection rating	IP 68





LEVEL CONTROL UNIT Code: 66637

91.5

52.5

0 00000

LEVEL CONTROL SENSOR ADJUSTABLE Code: 67444















Level Control System

Complementary Products

COMPLEMENTARY PRODUCTS WIND CONTROL SYSTEM

This wind control system is the best way of avoiding water loss from jets, thus preventing the area around a fountain and the spectators of a fountain display from getting wet due to the action of the wind.

It can be run in three modes depending on wind speed: normal, reduced fountain jet height and off in case of very strong wind.

WIND CONTROL SENSOR	Code: 66577	
Dimensions (L x W x H) [mm]	5 6 6	100 × 100 × 135

Range [m/s]	2 - 55		
Voltage [V]	5 - 15 VDC		
Output [Hz]	0 – 210		
Cable included	3 × 0,5 20 m		
Material	ABS		
Weight [kg]	1,2		
Protection rating	IP 65		

WIND CONTROL SENSOR



WIND CONTROL UNIT Code: 66	578
Dimensions (L x W x H) [mm]	53 × 66 × 92
Range [m/s]	Adjustable
Voltage [V]	230 VAC
Inputs	PNP/NPN or potential free contact
Outputs	3 relay outpus up to 6A
Display	LCD
LED Indicator	1 power, 3 outputs
Material	Plastic housing
Mounting	DIN rail
Protection rating	IP20

WIND CONTROL UNIT





Wind Control System

Complementary Products

COMPLEMENTARY PRODUCTS PIPE FITTING



Pipe fittings are the best way of connecting pipes through the wall or the floor of a fountain.

Available in standard sizes from 1"to 4".

All models are extremely robust and resistant to oxidation because they are made entirely of AISI 316 stainless steel.

PIPE FITTING FL-FL



PIPE FITTING FL-F



PIPE FITTING							
Code		L [mm]	А	B [mm]	С	D	E
66630	PIPE FITTING FL-FL 3"	220	80	88,9	110	120	-
66631	PIPE FITTING FL-FL 4"	220	100	114,3	135	145	-
66632	PIPE FITTING FL-M 3"	220	3"	88,9	110	120	80
66633	PIPE FITTING FL-M 4"	220	4"	114,3	135	145	100
66634	PIPE FITTING FL-F 3"	220	3"	100	100	120	80
66635	PIPE FITTING FL-F 4"	220	4"	125	126	145	100

PIPE FITTING FL-M



Pipe fittings are the best way of connecting pipes through the wall or the floor of a fountain.

Available in standard sizes from 1" to 4".

All models are extremely robust and resistant to oxidation because they are made entirely of AISI 316 stainless steel.

PIPE FITTING M-M



PIPE FITTING F-F



PIPE FITTING M-F



COMPLEMENTARY PRODUCTS PIPE FITTING



PIPE FITTIN	IG					
Code		L [mm]	А	B [mm]	C [mm]	D [mm]
66615	PIPE FITTING M-M 1"	220	1"	33,4	45	70
66616	PIPE FITTING M-M 1-1/2"	220	1 1/2"	48,3	60	75
66617	PIPE FITTING M-M 2"	220	2"	60,3	72	80
66618	PIPE FITTING M-M 3"	220	3"	88,9	100	120
66619	PIPE FITTING M-M 4"	220	4"	114,3	126	145
66620	PIPE FITTING F-F 1"	220	1"	40	50	70
66621	PIPE FITTING F-F 1-1/2"	220	1 1/2"	55	65	110
66622	PIPE FITTING F-F 2"	220	2"	70	85	120
66623	PIPE FITTING F-F 3"	220	3"	100	125	150
66624	PIPE FITTING F-F 4"	220	4"	125	145	160
66625	PIPE FITTING M-F 1"	220	1"	40	45	70
66626	PIPE FITTING M-F 1-1/2"	220	1 1/2"	55	80	110
66627	PIPE FITTING M-F 2"	220	2"	70	80	110
66628	PIPE FITTING M-F 3"	220	3"	100	100	120
66629	PIPE FITTING M-F 4"	220	4"	125	126	145

COMPLEMENTARY PRODUCTS **CABLE INLET** FITTING 1 - 2" FEMALE THREAD



Cable inlet fitting 2" threaded for cable gland for wires of different diameter depending on the model. Made with AISI-316 stainless Steel and nickel pated brass. Works as a cable inlet fitting for 2" pipes.

CABLE INLET FITTING 1 - 2" FEMALE THREAD	72049	73350	
Dimensions (L x W x A) [mm]	70 × 64 × 58	70 × 64 × 65	
Cable diameter [mm]	5-14	11-20	
Connection	2" G	2" G	
Material	Stainless Steel 316 / Nickel plated brass	Stainless Steel 316 / Nickel plated brass	

CABLE INLET FITTING 1 - 2" FEMALE THREAD







Prefilter LFS are mounted on the inlets of the suction lines to protect devices and water circuit from coarse debris.

Is highly versatile because it can be installed on the pipe directly and bolt it easily to the floor.

It has a large filter surface, so increases highly filter clogging time.

It is a very robust and resistant to rusting model manufactured entirely in AISI 316 stainless steel.

PREFILTER LFS Code: 73348	
Dimensions (L x W x H) [mm]	440× 440 × 370
Connection DN150	
Filter surface [m2]	1
Particle strainer [mm]	5
Material	AISI 316 stainless steel
Weight [kg	4,5 kg







PREFILTER LFS



COMPLEMENTARY PRODUCTS PRESSURE HOLDING VALVE

Pressure holding valve to install in manifolds with several controlled outputs. With this valve it is possible to maintain the pressure in the manifold, regardless of the open outputs.

With this valve is also possible to protect the pump against overload and the line of excessive pressures, in addition of ensuring a minimum flow.

It is a very robust and resistant to rusting model manufactured entirely in AISI 316 stainless steel.

PRESSURE HOLDING VALVE Co	de: 73349
Dimensions (L x W x H) [mm]	385 × 170 x170
Connection	3"M
Maximum flow [l/min]	720
Maximum pressure [bar]	2.2
Material	AISI 316 Stainless steel







Pressure Holding Valve

Complementary Products

COMPLEMENTARY PRODUCTS OVERFLOW



OVERFLOW	66612	66613	
Dimensions (L x W x H) [mm]	200 × 150 × 96	250 × 179 × 104	
Aspiration Flow 0,5 m/s [m³/h]	4,5	10	
Connection	2" G	3" G	
Material	Stainless Steel 316	Stainless Steel 316	

This overflow is suitable for any type of fountain. It is ideal for keeping the water level stable at all times and avoiding flooding.

It is available in two different models, depending on the surface of the fountain. Both models are made of AISI 316 stainless steel to ensure high protection against rust and weathering.

OVERFLOW 200 66612



OVERFLOW 250 66613

100000000



This overflow is suitable for any type of fountain. It is ideal for keeping the water level stable at all times and avoiding flooding.

It is available in two different models, depending on the surface of the fountain.

The standard model is manufactured between 10 and 100 centimeters, with the possibility of other dimensions on request.

Both models are made of AISI 316 stainless steel to ensure high protection against rust and weathering



ABIENT - COL NW ABIENT - COL NW R. EXT 3' W. BSP	
	* Product Upon Request

OVERFLOW 66610LXXXX 66611LXXXX Dimensions (L x W x H) [mm] 105 × 105 × (100-1000) 130 × 130 × (100-1000) Aspiration Flow 0,5 m/s [m3/h] 4,5 10 Connection 2" G 3" G Stainless Steel 316 Stainless Steel 316 Material

66611LXXXX **OVERFLOW 3**"



S

Н



COMPLEMENTARY PRODUCTS **FLOOR** DRAIN



This drain is installed on the floor of the pool of the fountain and it's ideal for ensuring fountain water emptying or return.

It is a very robust and resistant to oxidation model manufactured entirely in AISI 316 stainless steel.

FLOOR DRAIN Code: 66614	
Dimensions (L x W x H) [mm]	162 × 162 × 116
Aspiration flow 0,5 m/s [m³/h]	4,5
Connection	2" G
Material	Stainless Steel 316

FLOOR DRAIN



The Junction Boxes are the best way to ensure watertight connections between cable inside the pool of the fountain. With its original design allow the connection of different devices with the same Junction Box.

It is a very robust and resistant to oxidation model manufactured entirely in AISI 316 stainless steel.

	66602	66603	66604	66605		
Dimensions (L x W x H) [mm]	224×190×127	240×224×127	324×290×127	324×290×139		
Number of inlets	6	10	16	32		
Wire diameter	5-14	5-14	5-14	5-14		
Material		Stainless steel 316				
Protection class	IP 68	IP 68	IP 68	IP 68		

ASTRALPOOL



COMPLEMENTARY PRODUCTS

JUNCTION BOXES

JUNCTION BOX - 6 66602

JUNCTION BOX - 10 66603







JUNCTION BOX - 16 66604









* Product Upon Request

COMPLEMENTARY PRODUCTS CABLE INLET FITTING



The Cable inlets Fittings are the best way to ensure watertight connections with cable through the walls of the fountain. With its original design allow the connection of different devices with the same Cable Inlet Fitting.

It is a very robust and resistant to oxidation model manufactured entirely in AISI 316 stainless steel.

	66598	66599	66600	66601
Dimensions (L x W x H) [mm]	70×48×151	80×70×151	175×175×181	215×215×181
Connection	1"G	2"G	3"G	4"G
Number of inlets	1	3	5	8
Wire diameter	5-14	5-14	5-14	5-14
Material	erial Stainle		steel 316	
Protection class	IP 68	IP 68	IP 68	IP 68

CABLE INLET FITTING - 1 66598

CABLE INLET FITTING - 3 66599







Ø 114

Ø 89

R.EXT 3" W.BST

CABLE INLET FITTING - 8 66601















The Cable inlet Fitting Box are the best way to ensure watertight connections with cable through the walls of the fountain and at the same time interconnect different devices.

It is a very robust and resistant to oxidation model manufactured entirely in AISI 316 stainless steel.

	66606	66607	66608	66609	
Dimensions (L x W x H) [mm]	290×290×253	290×290×265	290×290×270	290×290×282	
Connection	3"G	3"G	4"G	4"G	
Number of inlets	16	32	16	32	
Wire diameter	5-14	5-14	5-14	5-14	
Material		Stainless steel 316			
Protection class	IP 68	IP 68	IP 68	IP 68	

CABLE INLET FITTING BOX 66606







CABLE INLET FITTING BOX 66608



CABLE INLET FITTING BOX 66607







COMPLEMENTARY PRODUCTS ASTRALPOOL



COMPLEMENTARY PRODUCTS **ELECTRIC** VALVES CPV

ELECTRIC VALVES

Sizes	¾", 1", 1½", 2", 3" BSP female		
Options	24 VAC		
Minimum flow	0,5 m3/h		
Working pressure	0,7 - 10 bar		
Material	Nylon reinforced		
Control	Electric - solenoid 2 ways		
Flow control	YES		
Other characteristics	Without pipes or external accessories Compact construction Bolt closing cover Self cleaning hole		

ELECTRIC VALVES 24VAC	
CPV2071B - Electric valve 3/4"	56113
CPV2101B - Electric valve 1"	56114
CPV2151B - Electric valve 1"1/2	56115
CPV2201B - Electric valve 2"	56116
CPV1300B - Electric valve 3" (no flow control)	57641
CPV1301B - Electric valve 3"	60556

WORKING



Open Position

Closed Position

The internal restriction continuously allows line pressure into the control chamber. The solenoid controls outflow from the control chamber. When the solenoid is closed it causes pressure to accumulate in the control chamber, therefor forcing the valve to close.

COMPONENTS



	COMPONENT	MATERIAL
1	Bolts and nuts	Stainless steel
2	Solenoid	
3	Manual override handle	
4	Needle	
5	Flow control	
6	Auxiliary closing spring	Acero inoxidable
7	Diaphragm	NBR
8	Internal restriction	
9	Body	Nylon reinforced

Opening the Solenoid releases more flow

from the control chamber than the restriction can

allow in. This causes the accumulated pressure

in the control chamber to drop, enabling the line

pressure acting on the plug to the valve.



Electric Valves CPV

Complementary Products

COMPLEMENTARY PRODUCTS **ELECTRIC** VALVES CPV

FLOW DIAGRAMM



	PRESSURE LOSS	3/4 "	1"	1½"	2"	3"
•	2	0,06	0,04			
	3	0,125	0,09	*		
	4	0,2	0,15	*		
	5	0,3	0,25			
	6	0,5	0,35			
	7	0,7	0,5	0,04		
	8	0,8	0,6	0,05		
	9	1	0,7	0,07	0,04	
	10		1	0,09	0,05	
	15			0,175	0,1	0,06
	20			0,3	0,2	0,1
	30			0,7	0,4	0,2
	40				0,7	0,3
	50					0,4

PRESSURE LOSS	DN20 - ¾"	DN25 - 1"	DN40 - 11/2"	DN50 - 2"	DN80 - 3"
Kv (m³/h)	9	10,5	37	47	100

KV VALUE:

Flow V (water flow) in m3/h in a temperature between 5 to 30 °C, through a velve with a pressure loss of $\Delta p = p1-p2=1$ bar

DIMENSIONS	DN20	DN25	DN40	DN50
L (mm)	110	110	160	170
H (mm)	115	115	180	190
R (mm)	22	22	35	38
W (mm)	78	78	125	125
Weight (kg.)	0,35	0,33	1	1,1







The Swivel is a perfect adapter for all types of nozzles. Corrects the unevenness produced during the development of the work. The Swivel also allows positioning any type of nozzle in any desired angle.

SWIVEL	66930	66929	73347
Dimensions (A x B) [mm]	70 × 68	93 × 89	49 × 85
Water connections (C)	1" G	1-1/2" G	1" G
Max working angle	+22° / -22°	+23° / -23°	+18° / -18°
Material	AISI 316	AISI 316	Nickel plated brass
Weight [kg]	0,6	1	0,4

SWIVEL Code: 66930 - 66929



COMPLEMENTARY PRODUCTS SWIVEL



PROJECT VEW







COMPLEMENTARY PRODUCTS

201	لنت
8	Ş
(in)	Sec. Sec. Sec. Sec. Sec. Sec. Sec. Sec.



DIMENSIONS	Н		W	W		Х		D		
DIVILINGIONS	mm	in	mm	in	mm	in	mm	in		
3/4"	173	7	185	7	158	6	83	3		
1"	173	7	190	7	168	7	133	5		
1"1/4	202	8	231	9	231	9	133	5		
1"1/2	202	8	231	9	231	9	115	5		
2"	248	10	270	11	267	11	144	6		

LF FILTERS



	Connection	Maximum flow	Filtration surface (mesh)	Maximum temperature / pressure
	3⁄4"	5 m³/h - 22 gpm	160 c² - 25 in2	8 bar/116 psi - 60 oC/140 oF
	1"	6 m³/h - 26 gpm	160 cm² - 25 in2	8 bar/116 psi - 60 oC/140 oF
CEPEX MANUAL LF FILTERS	11/4"	10 m³/h - 44 gpm	265 cm² - 41 in2	8 bar/116 psi - 60 oC/140 oF
LF FILIERS	11/2"	14 m³/h - 62 gpm	265 cm² - 41 in2	8 bar/116 psi - 60 oC/140 oF
	2"	25 m³/h - 110 gpm	485 cm² - 75 in2	8 bar/116 psi - 60 oC/140 oF



MESH LF FILTERS	CODE
CEPEX MANUAL LF FILTER 3/4"B SCREEN 130MICRON - Q 5M3/H	34910
CEPEX MANUAL LF FILTER 1"B SCREEN 130 MICRON - Q 6M3/H	34911
CEPEX MANUAL LF FILTER 1 1/4"B SCREEN 130M - Q 10M3/H	04132
CEPEX MANUAL LF FILTER 1 1/2"B SCREEN 130M - Q 14M3/H	04133
CEPEX MANUAL LF FILTER 2"B SCREEN 130 MICRON - Q 25M3/H	34912

	Connection	Maximum flow	Filtration surface (mesh)	Maximum temperature / pressure
CEPEX MANUAL HFL FILTERS	2"	30 m3/h - 132 gpm	650 cm2 - 101 in2	6 bar/90 psi - 60 oC/140 oF
	2" LARGE	30 m3/h - 132 gpm	960 cm2 - 149 in2	6 bar/90 psi - 60 oC/140 oF
	3"	50 m3/h - 220 gpm	650 cm2 - 101 in2	6 bar/90 psi - 60 oC/140 oF
	3" large	50 m3/h - 220 gpm	960 cm2 - 149 in2	6 bar/90 psi - 60 oC/140 oF

Standard: 130 microns - 8 bar Ask for other options

Ask for other option

PRESSURE LOSS bar psi 1.00 14.5 0.10 0.01 m∛h 5 20 50 22 88 220 gpm malla 2″ — 3″ 2" LARGE 3" LARGE

MESH HFL FILTERS	CODE
CEPEX MANUAL HLF FILTER 2 B SCREEN 130 MICRON 30 M3/H	62271
CEPEX MANUAL HLF FILTER 2LARGE B SCREEN 130M 30M3/H	62273
CEPEX MANUAL HLF FILTER 3 B SCREEN 130 MICRON 50M3/H	62275
CEPEX MANUAL HLF FILTER 3LARGE B SCREEN 130 MICRON 50M3/H	62277

COMPLEMENTARY PRODUCTS



	Н		V	W		<	D	
DIVIENSIONS	mm	in	mm	in	mm	in	mm	in
2"	445	17.5	286	11.2	75	3.0	231	9.1
2" LARGE	595	23.4	286	11.2	75	3.0	231	9.1
3"	495	19.5	336	13.2	110	4.3	231	9.1
3" LARGE	645	25.4	336	13.2	110	4.3	231	9.1

HFL FILTERS





PUMPS VICTORIA PLUS SILENT PUMP

A self-priming pump with single-phase and three-phase motors of 1/2 to 3 HP. A prefilter is mounted on the body of the pump to prevent foreign bodies from entering it that may damage its hydraulic parts. The motors supplied come with an IP-55 protection rating and have been prepared to withstand hot environments and high levels of humidity. The main characteristics of Victoria Plus Silent are: Optional:

60 Hz pumps (code XXXX-0810).

VICTORIA PLUS SILENT PUMP

- Low noise level: between 61 dBA-70 dBA.

- Easy to use: Prefilter cap with 2 levers included (no spanner needed).

- Compatibility: Fully compatible in pools fitted with a Victoria Plus pump. Larger front bearing for improved axial thrust.

	Code	Standard Pack	Standard Weight kg	Standard Volume m ³
10.000 l/h 0,43 kW (1/2 HP) 230 V II	65557	1	12	0.07
10.000 l/h 0,43 kW (1/2 HP) 230/400 V III	65558	1	12	0.07
11.000 l/h 0,61 kW (3/4 HP) 230 V II	65560	1	13	0.07
11.000 l/h 0,60 kW (3/4 HP) 230/400 V III	65561	1	13	0.07
16.000 l/h 0,78 kW (1 HP) 230 V ll	65562	1	14	0.07
16.000 l/h 0,76 kW (1 HP) 230/400 V III	65563	1	14	0.07
21.500 l/h 1,10 kW (1,5 HP) 230 V II *	65564	1	14	0.07
21.500 l/h 1,10 kW (1,5 HP) 230/400 V III *	65565	1	14	0.07
26.000 l/h 1,46 kW (2 HP) 230 V II *	65566	1	17	0.07
26.000 l/h 1,46 kW (2 HP) 230/400 V III *	65567	1	17	0.07
34.000 l/h 2,20 kW (3 HP) 230/400 V II *	65569	1	18	0.07
34.000 l/h 2,20 kW (3 HP) 230/400 V III *	65570	1	18	0.07
*Set of PVC accessories (not included with the pump)	67655	1	-	-

VICTORIA PLUS SILENT PUMP PERFORMANCE CURVE







				Di	mensior	IS			
Code	Α	В	С	D	D1	E	F	Н	I
65557	581	281	246	ent	2" GAS	359	322	164	254
65558	581	281	246	Sil	2" GAS	359	322	164	254
65560	581	281	246	Plus	2" GAS	359	322	164	254
65561	581	281	246	ā.	2" GAS	359	322	164	254
65562	581	281	246	e Victo	2" GAS	359	322	164	254
65563	581	281	246	> >	2" GAS	359	322	164	254
65564	615	281	246	on th	2" GAS	359	356	164	254
65565	615	281	246	σ	2" GAS	359	356	164	254
65566	615	281	246	Jred	2" GAS	359	356	164	254
65567	615	281	246	Ē	2" GAS	359	356	164	254
65569	646	281	246	External Threa	2" GAS	359	387	164	254
65570	615	281	246	Ext	2" GAS	359	356	164	254

Code	Power CV/HP	Voltage V	Max. H m	RPM	Nom. Q m³/h	Nom. H m	Weight kg	Volume m³
65557	1/2 CV II	230V	14	2810	11	8	10	- - -
65558	1/2 CV III	230/400V	14	2825	11	8	12	a • •
65560	3/4 CV II	230V	15	2802	11	10	10	0 9 9 9
65561	3/4 CV III	230/400V	15	2810	11	10	13	0 0 0 0
65562	1 CV II	230V	17	2810	16	10	- 14	0 5 6
65563	1 CV III	230/400V	17	2810	16	10		0.07
65564	1.5 CV II	230V	18	2800	22,5	10	14 :	0.07
65565	1.5 CV III	230/400V	18	2810	22,5	10	0 0 0 0	0 9 9
65566	2 CV II	230V	18	2860	26,5	10	47	0 5 6
65567	2 CV III	230/400V	18	2800	26,5	10	17	0 8 9 9
65569	3 CV II	230V	21	2827	34	10	18	0 8 9
65570	3 CV III	230/400V	21	2780	34	10		0 8 8







Pumps

SELF-PRIMING PUMPS

High performance plastic self-priming pump for high flow rates (1500 rpm).

- 3 power modes: 3 HP, 4 HP and 5.5 HP.
- Low sound level: as low as 59 dBA
- Hydraulic efficiency without prefilter 78% (as per ISO 9906 standard).
- High quality mechanical seal for salt water.
- IEC high efficiency motors (IE3).
- Standard motor shaft (compatibility with any pump manufacturer).
- Product with GS marking
- Pump comes with pre-filter (in 2 packages: pump + prefilter).

	Code	Standard Pack	Standard Weight kg	Standard Volume m³
Kivu 2,20 kW (3 HP) 230/400V 50Hz + prefilter	66047	1	56.4	0.35
Kivu 2,20 kW (3 HP) 400/690V 50Hz + prefilter	63042	1	56.4	0.35
Kivu 3,00 kW (4 HP) 230/400V 50Hz + prefilter	66048	1	59.4	0.35
Kivu 3,00 kW (4 HP) 400/690V 50Hz + prefilter	63043	1	59.4	0.35
Kivu 4,10 kW (5.5 HP) 230/400V 50Hz + prefilter	66049	1	66.4	0.35
Kivu 4,10 kW (5.5 HP) 400/690V 50Hz + prefilter	63044	1	66.4	0.35

Code	Power	Α	Da	Di	DNa	DNi	С	C1	Е	F	G	Н	I	J	Κ	L	М	Ν	0	Ρ	Q	R	Ma	Mi
	HP											m	ım											
63042 66047	3	440	-	220	-	100 - 4"	462	610	279	206	480	313	320	561	29.5	882	157	181.5	100	460	154	590	-	180
63043 66048	4	440	-	220	-	100 - 4"	462	610	279	206	480	313	320	561	29.5	882	157	181.5	100	460	154	590	-	180
63044 66049	5.5	440		220	-	100 - 4"	462	610	279	206	480	313	345	561	156	906	157	181.5	100	460	154	621	-	180

Flanges drilled to standard DIN-2501. Quick closing lid. Polypropylene basket. Drain plug. Maximum working pressure 1.5 bar.

	Code		Standard Weight kg	Standard Volume m³
25 I Capacity 6" Connections DN 150	56733	1	9.9	0.08

Optional: 60 Hz pumps (code XXXX-0810).

KIVU PUMP









KIVU STRAINERS









Kivu strainers



AstralPool Toolbox app for IOS and Android

Kivu Pump

Self-Priming Pumps

GRAPH SHOWING PERFORMANCE OF PUMPS WITHOUT PREFILTER

GRAPH SHOWING PERFORMANCE OF PUMPS WITHOUT PREFILTER

Power/Flow rate

Pressure/Flow rate





SELF-PRIMING PUMPS

High performance plastic centrifugal pump for public pools that works at 1500 rpm.

- 3 power modes: 7.5 HP, 10 HP and 15 HP.
- Low sound level: as low as 66 dBA
- Hydraulic efficiency without prefilter 85% (9906 ISO standard).
- High quality mechanical seal for salt water.
- IEC high efficiency motors (IE3).
- Standard motor shaft (compatibility with any pump manufacturer).
- Product with GS marking
- Pump comes with pre-filter (in 2 packages: pump + prefilter).

	Code	Standard Pack	Standard Weight kg	Standard Volume m³
Kivu 5,60 kW (7.5 HP) 230/400 V 50Hz + prefilter	56633	1	107.4	0.43
Kivu 5,60 kW (7.5 HP) 400/690 V 50Hz + prefilter	56634	1	107.4	0.43
Kivu 7,50 kW (10 HP) 230/400 V 50Hz + prefilter	56635	1	117.9	0.45
Kivu 7,50 kW (10 HP) 400/690 V 50Hz + prefilter	56637	1	117.9	0.45
Kivu 11,20 kW (15 HP) 230/400 V 50Hz + prefilter	56638	1	151.2	0.49
Kivu 11,20 kW (15 HP) 400/690 V 50Hz + prefilter	56639	1	151.2	0.49

Code	Power	А	Da	Di	DNa	DNi	С	C1	Е	F	G	Н	I	J	К	L	М	Ν	0	Ρ	Q	R	Ma	Mi
	HP											m	m											
56633 56634	7.5	653	285	250	150 - 6"	125 - 5"	446	688	279	206	290	540	410	653	141	1215	157	192	208	550	157	815	240	210
56635 56637	10	653	285	250	150 - 6"	125 - 5"	446	688	279	206	290	540	445	653	141	1250	157	192	208	550	157	850	240	210
56638 56639	15	653	285	250	150 - 6"	125 - 5"	446	688	279	206	290	670	510	653	271	1315	157	192	208	550	157	915	240	210

Flanges drilled to standard DIN-2501. Quick closing lid. Polypropylene basket. Drain plug. Maximum working pressure 1.5 bar.

	Code			Standard Volume m³
25 I Capacity 6" Connections DN 150	56733	1	9.9	0.08

Optional: 60 Hz pumps (code XXXX-0810).

KIVU PUMP









KIVU STRAINERS





Kivu strainers



AstralPool Toolbox app for IOS and Android

Kivu Pump

Self-Priming Pumps

GRAPH SHOWING PERFORMANCE OF PUMPS WITHOUT PREFILTER



Power/Flow rate

GRAPH SHOWING PERFORMANCE OF PUMPS WITHOUT PREFILTER



SELF-PRIMING PUMPS **SUBMERSIBLE PUMP DF** WITH PREFILTER



Submersible DF pumps has a prefilter incorporated which helps to the correct working of the device. It has a large filter surface, so increases highly filter clogging time.

Incorporates supports to ease horizontal pump installation.

There are available some pump models according to the needs of each installation. It is a very robust and resistant to rusting model manufactured in AISI 304 stainless steel.

		70173	70175	70177	70179	70180	70181	70184	70190
Dimensions	Lenght (L)	402	417	447	447	402	417	447	447
	Width (W)	232	232	232	232	232	232	232	232
	Height (H)	234	234	234	234	234	234	234	234
Voltaje Nominal [V]		230	230	230	230	400	400	400	400
Potencia nomi	nal [kW]	0,55	0,75	1,1	1,5	0,55	0,75	1,1	1,5
Maximum Flow	v [l/min]	250	325	375	420	250	325	375	420
Maximum head [m]		10,9	14	16,1	20,6	10,9	14	16,1	20,6
Hydraulic connection		1 <i>1</i> ⁄2" G	11⁄2" G						
Minimum water depth [mm]		300	300	300	300	300	300	300	300

SUBMERSIBLE PUMP DF WITH PREFILTER





Submersible Pump Df With Prefilter

Self-Priming Pumps

GRAPH SHOWING PERFORMANCE OF PUMPS



STRAINERS ARALS STRAINERS



Housing and cover in cast iron. AISI-304 stainless steel strainer basket.
Flange connection are manufactured in accordance with DIN-2501
Standard. Maximum working pressure 2.5 bar.

ARALS STRAINERS 11 I	Code		Standard Weight kg	Standard Volume m ³
Flanges DN 65 (21/2") DN 65 (21/2")	20026	1	35	0.051
Flanges DN 100 (4") DN 100 (4")	20029	1	35	0.051
Flanges DN 125 (5") DN 125 (5")	20030	1	35	0.051
Flanges DN100 (4") DN 80 (3")	20032	1	35	0.051
Flanges DN 125 (5") DN 100 (4")	20033	1	35	0.051

ARALS STRAINERS 37 I	Code	Standard Pack	Standard Weight kg	Standard Volume m³
Flanges DN 150 (6") DN 150 (6")	01268	1	129	0.319

ARALS STRAINERS 11 I



VDVIC	STRAIN	DS 371
ARALO	STRAIN	ERO 07 I





Code	Capacity	Input connection Outlet connection Dimensions (mm					Outlet connection				այ							
	e ap aong	Da		Pa	(Qa	Di	Di	Pi		Çi	ļ						
Aral	I	(mm)	DNa	(mm)	No	Ø (mm)	(mm)	. DNi I.)	(mm)	No	Ø (mm)	Α	В	С	E	F	G
20026	11	185	65-2 ¹ / ₂ "	145	4	18	185	65-2 ¹ / ₂ "	145	4	18	315	392	295	159	-	-	
20029	11	220	100-4"	180	8	18	220	100-4"	180	8	18	315	392	295	159	-	-	
20030	11	250	125-5"	210	8	18	250	125-5"	210	8	18	315	392	295	159	-	-	
20032	11	220	100-4"	180	8	18	200	80-3 "	160	8	18	315	392	295	159	-	-	
20033	11	250	125-5"	210	8	18	220	100-4"	180	8	18	315	392	295	159	-	-	
01268	37	285	150-6"	240	8	22	285	150-6"	240	8	22	649	600	542	250	257	507	

Laminated filter made of fibreglass and polyester. Grey in colour, polypropylene base, new boltless lid, water drainage plug, flowmeter and side-mounted multiport valve. Maximum pressure of 2.5 kg/cm^2 . Top filtration speed of 50 m³/h/m².

WITH SIDE-MOUNTED MULTIPORT VALVE	Code		Standard Weight kg	Standard Volume m³
With side-mounted multiport valve	•	•	m 6 6	
5000 l/h Ø 350 mm outlet 11/2"	00497	1	18	0.13
8000 l/h Ø 450 mm outlet 11/2"	00498	1	21	0.23
9000 l/h Ø 500 mm outlet 11/2"	19781	1	23	0.28
14000 l/h Ø 600 mm outlet 11/2"	00499	1	28	0.39
15000 l/h Ø 650 mm outlet 11/2"	21071	1	29	0.45
21000 l/h Ø 750 mm outlet 2"	00500	1	37	0.62

WITH MULTIPORT VALVE	00497	00498	19781	00499	21071	00500
Ø D (mm)	350	450	500	600	650	750
H (mm)	780	795	770	850	880	945
M (mm)	420	430	415	455	480	555
N (mm)	295	305	290	330	355	325
Connections	11/2"	11/2"	11/2"	11/2"	11/2"	2"
Flow (m³/h) at 50 m³/h/m²	5	8	9	14	15	21
Pool volumen (m³) (8 h)	40	64	72	112	120	168
Sand load (kg)	50	70	90	125	200	290
Grade 1 glass load (57011) (kg)	35	49	63	88	140	203
Grade 2 glass load (57012) (kg)	9	13	17	24	38	258
Maximum pressure (kg/cm²)	2.5	2.5	2.5	2.5	2.5	2.5
Net weight (kg)	18	21	23	28	29	37
Package volume (m³)	0.13	0.23	0.28	0.39	0.45	0.62

ASTER FILTERS



LAMINATED FILTERS ASTER FILTERS



DRAIN GRILLE DRAIN GRILLE IN STAINLESS STEEL



Designed for fountains. Support frame and grille in polished stainless steel. Supplied with fixing screws. Other sizes can be made to order.

AISI-316		Code		Standard Weight kg	Standard Volume m³
Size (mm)	Max. recommended flow rate				
200×200	15 m³/h (0,5 m/s)	30764	1	1.2	0.01
300×300	43 m³/h (0.5 m/s)	30765	1	2.2	0.01
400×400	83 m³/h (0,5 m/s)	30766	1	4.0	0.03
500×500	136 m³/h (0,5 m/s)	30767	1	4.5	0.04

Outer 11/2" thread. Made of AISI-316 stainless steel. Max. recommended flow rate compliant with standard EN 13451-3: 4.5 m³/h. Ø 20 mm eyeball.

	Code			Standard Volume m³
Length 35 mm	32994	1	0.3	0.001
Length 50 mm	16325	1	0.3	0.001
Length 70 mm	16326	1	0.5	0.001

STAINLESS STEEL INLETS BRETURN INLET



This robust waterproof junction allows to make IP68 connections, both for electrical and communication cables.

It is available in two different models, depending on the cable diameter to be connected.

Both models are made of AISI 316 stainless steel to ensure high protection against rust and weathering.

WATERPROOF JUNCTION	70685	70684
Dimensions (L x W x H) [mm]	171 × 76 × 76	171 × 76 × 76
Cable diameter range [mm]	14 - 5	20 - 11
Material	SS 316 / Brass / TPE	SS 316 / Brass / TPE

WATERPROOF JUNCTION Code: 70685

de. 70000





WATERPROOF JUNCTION Code: 70684





COMPLEMENTARY PRODUCTS ASTR WATERPROF JUNCTION



DOSING PUMPS OPTIMA NEXT CONSTANT FLOW RATE ANALOGUE DOSING PUMP



The OPTIMA dosing pump represents the development of more than 30 years of experience in the automatic dosing field. This new series reduces the number of pumps required to meet the various dosing needs.

The OPTIMA dosing pump series, with its new power supply technology from 90, VCA to 265 VCA and at 50-60 Hz, ensures a precision and reliability never seen before.

Integration of many functions due to its simple programming, an alphanumeric display, the possiblity of multilingual programming of the menu and a new technology which permit controlled flow rate and back pressure. Allows to use the same model for various applications providing a great versatility.

Systems produced according to EC standards. IP-65 protection rating. Electrical power supply of 90-265 VCA 50/60 Hz. Materials in contact with the chemical product are made of polypropylene, Viton, Teflon and PVC (other materials possible upon request). Anti-acid plastic bodywork. Moisture-resistant membrane buttons. Built-in bleed valve. No lubrication necessary and little maintenance.

The flow rate is fully adjustable from the flow meter. Power supply from 90 to 230 VCA at 50-60 Hz without plug.

	Code		Standard Weight kg	Standard Volume m ³
Adjustable Optima manual pump at 8 bar and 5 I/h	66164	1	-	-

The panels in the CONTROLLER range are fully equipped and assembled systems. They are therefore ideal for use in water treatment.

Their simple, compact design makes installation and start-up extremely easy.

They come with all of the components and accessories required for rapid assembly. All assemblies are made of PVC sheets, in various sizes depending on the model.

General technical features

- Range of available sizes depending of the probe selected.
- Range available for free chlorine: 0-2, 0-5 0-10, 0-20 and 0-200 ppm. - pH range: 0–14.
- ORP range: +/-1500 mV.
- Temperature range: 0–50oC.
- Measurement of stable chlorine with low pH dependence.
- Self-calibration of all sizes.
- Alarm signal if water flow is insufficient.
- Instrument with IP65 protection rating.
- 250 V-10 A relays for connecting dosing pumps or salt chlorinators.
- 4-20 mA analogue outlets with repeat signal or manifold for proportional pumps.
- Power supply: 230 V / 50 Hz.
- Setpoints and programmable alarms.
- Pump pause function during calibration and for stopping flow.
- Temperature readings and readjustment (automatic with PT100 probe included).
- Three types of setpoint settings. On/Off, Proportional in Time and Proportional by Pulses.
- RS485 communications port.

Components included in the assembly:

- Methacrylate probe holder, with flow regulator, sample taking valve and flow sensor.
- Filter holder and 80 micron filter cartridge for water inlet.
- DPD calibration standard solutions.
- Assembly accessories, and instruction and installation manual.
- Sensors depending on version.



AUTOMATIC REGULATION AND CONTROL EQUIPMENT CONTROLLER





ASTRALPOOL

Fluidra Connect compatible



DOSING EQUIPMENT **3.5 KG DOSSI-3** Chlorine and bromine Feeder



INSTALLATION DIAGRAM OF CHLORINE/BROMINE DOSING UNITS AND AUTOMATIC REGULATING AND CONTROL EQUIPMENT

Automatic regulating and control equipment Dosing pump Firegulation Chlorine dispensor Chlorine and bromine feeder. Manufactured from unalterable plastic materials (ABS). Approximate capacity: 3.5 kg of tablets. Lid closing with double safety system. Easy to operate regulation valves. For pools up to 60 m^3 with chlorine and up to 30 m^3 with bromine. Height: 405 mm.

	Code			Standard Volume m³
Dosi-3 in-line for pools up to 60 m ³ . For direct connection to pipework with 1 1/2" connectors	24429	1	1.81	0.03
Dossi-3 off-line for pools up to 60m ³ . For by-pass connection with flexible tube	24430	1	1.90	0.031

3.5 KG DOSSI-3 CHLORINE AND BROMINE FEEDER Code: 24429



3.5 KG DOSSI-3 CHLORINE AND BROMINE FEEDER Code: 24430



Bromine and Chlorine feeder. Manufactured from unalterable plastic materials (ABS). Approximate capacity: 5 kg of tablets for Dossi-5 kg. Supplied with two valves in order to stop the water flow. Height 486 mm and Ø 200 mm. Connections Ø 20 mm.

	Code	Standard Pack	Standard Weight kg	Standard Volume m³
Dossi-5 off-line for pools up to 100 \mbox{m}^3	01413	1	3.7	0.031

Volume of chlorine-treated pool		Volume of bromine-treated pools		
Dossi 5	20 m3 - 80 m³	4 m3³ - 50 m³		

DOSING EQUIPMENT DOSSI-5 OFF-LINE CHLORINE AND BROMINE FEEDER





Professional version of the very popular AquaForte Power UV-0	C. The
AquaForte Prime Power Signal UV-C is equipped with a LED tin	ner that
continuously displays the lamp status clearly in colour.	

LED status: green: everything okay; flashing green: almost end of lamp life; red: end of lamp life.

After lamp replacement, the timer can be reset so that the countdown starts again.

The unit is made of stainless steel and has 3 connections $(2 \times 63 \text{ mm} \text{ and } 1 \times \text{blind cover})$, plus 2 special hose connectors (32/38/40/50 mm) for even more installation options. The unit is equipped with a T5 lamp for optimum operation (9000 hours).

Comes with electronic ballast for optimum operation. Average lifespan of the ballast is \pm 5 years. The T5 lamp provides a radiation value of 25,000 microwatts. Working pressure maximum 2 bar. Keeps bacteria and algae under control.

ТУРЕ	ART NR.	MAX POND	MAX FLOW M ³ /H
Power Signal UV 75 watt	SB396	70 m³	20
Replacement lamp 75 Watt T5	SB619	-	-
Quartz glass	SB688A	-	-

POWER SIGNAL UV Code: SB396



Disinfection of pond water is the solution for preventing green pond water and is therefore indispensable in every pond. Why it is important to always use a UV-C unit in your pond:

- Rapid improvement of water quality.
- A crystal clear pond without the addition of chemicals.
- Protects fish and other pond life from pathogens.
- Environmentally friendly technology.
- Overdosing is not possible.
- Reduces the maintenance of your pond.

Redesigned electronic ballast has a signal lamp that indicates the status of the UV-C lamp:

- Green: everything okay
- Flashing green: lamp(s) almost at end of life
- Red: lamp(s) at end of life
- After lamp replacement the timer can be reset so the countdown starts again.

	BUSTER UV-C 140W AMALGAAM	BUSTER UV-C 420W AMALGAAM
Code	SB397	SB398
Rec. flow for 30 mJ/cm ²	23 m³/h	49 m³/h
Max. pressure	2,5 bar	2,5 bar
Max. flow	25 m³/h	49 m³/h
Diameter unit Ø	114 mm	219mm
Length unit	930 mm	930 mm
Diameter in-outlet Ø	2" male threaded	3" male threaded
Housing	316L	316L
Electronic ballast	230V AC 50/60Hz	230V AC 50/60Hz
Maximum current	0,7A	1,9A
Lamp power	140W	3 × 140W
Lamp	VGE T6 140W Amalgaam 4P	3× T6 140W Amalgaam 4P
Ambient temperature Timer Box	1-40 °C	1-40 °C
Lifespan lamp	16.000 h	16.000 h
Lamp status indicator	\checkmark	
Replace lamp alert	\checkmark	
Flow switch	\checkmark	\checkmark

AQUAFORTE PRIME NEW PRODUCT BUSTER UV-C UNITS



BUSTER UV-C 140W Code: SB397



BUSTER UV-C 420W Code: SB398



ASTRALPOOL



FLUIDRA IN THE WORLD

	\bigcirc		$\widehat{\bigtriangleup}$
AUSTRALIA Fluidra australia	111 Indian Drive, Keysborough, Victoria, 3173	00 6139554 2200	sales@astralpool.com.au
AUSTRIA SSA FLUIDRA ÖSTERREICH	Untersbergstraße 10, A-5082 Salzburg-Grödig (AUSTRIA)	0043 0624677000	office@ssa.co.at
BELGIUM astralpool belgique	Rue de la Glacerie 122 6180 Courcelles	00 32 71 45 24 08	belgique@fluidra.be
BOSNIA HERZEGOWINA Fluidra bh			
BRASIL Fluidra brasil	Rua João Voss Júnior, 23 - Barrio Guarani CEP: 88350-685 – Brusque/SC (BRAZIL)	00 55 47 3255.9700	vendas@fluidra.com.br
BULGARIA Fluidra balkans	191 " Golyamokonarsko shose" str. 4027 Plovdiv	359 32 950 023	sales@fluidrabalkans.com
CHILE Fluidra Chile	El Conquistador del Monte 4731 HUECHURABA, SANTIAGO (CHILE)	00 56 27400830	info@fluidra.cl
CHINA astralpool china	Room 1008, 10th Floor, Hongwell International - Plaza No 1602 Zhong Shan West Road - 200235 Shangai (CHINA)	00 86 2163910575	xiao.he@fluidra.com.cn
COLOMBIA Fluidra colombia	Km. 7 Autopista Medellín, Celta Trade Park, Lote 155, Bodega 1, Funza Cundinamarca. El código postal es: 250028	00 571 7021991	fluidracolombia@fluidra.com.co
CROATIA Fluidra adriatic	Kovinska 4a 1000 Zagreb (CROATIA)	00 385 17988790	info@fluidra.hr
CYPRUS ASTRALPOOL CYPRUS	Mantheou Mantheou 5, Industrial Area Ag. Athanasios 4101, Limassol (CYPRUS)	00 357 257 54424	info@astralpool.com.cy
CZECH REPUBLIC astral bazenove	Doubravice 86 25170 Dobrejovice Praha-Vychod (CZECH REPUBLIC)	00 420 323 638206	info@astralpool.cz
DENMARK Fluidra nordic	Kometvej 28 6230 Rødekro (DENMARK)	00 45 74 69 39 99	
EGYPT FLUIDRA EGYPT	Plot No.82, Qamaen El Geer, Industrial Zone - Third Colony, Qattameya, New Cairo, Cairo (Egypt)	00 20 1271779887	mnahhal@fluidraegypt.com
FRANCE Fluidra commercial france	Avenue Maurice Bellonte 66000 PERPIGNAN (FRANCE)	00 33 04 11 300 200	callcenter@fluidra.fr
GERMANY Fluidra deutschland Gmbh	Carl-Benz-StraBe 18 D-69493 Hirschberg	00 49-81 53-987490	info@fluidra.de
GREECE Fluidra hellas	FLUIDRA ΕΛΛΑΣ Α.Ε.περισσότερες πληροφορίεςΟ σταθμός είναι προσβάσιμος- Thesi Lakko Katsari Ασπρόπυργος 193 01	00 30 21 0559 4527	info@astralpool.gr
HUNGARY Fluidra magyarország	2311 Szigetszentmiklós Leshegy út 2-4., Magyarország (HUNGARY)	00 36 24525868	jdominguez@astralpool.hu
INDIA ASTRAL INDIA CERTIKIN INDIA	C-77, Ground Floor, DDA Shed, Near Crown Plaza Hotel, Okhla Industrial Area Phase-1, New Delhi- 110 021	011- 4905 4775	info@astralpool.in manuj@certikin.in
INDONESIA FLUIDRA INDONESIA	Pondok Indah Office Tower 1 Level 12 Suite 12 01 Jl. Sultan Iskandar Muda Kav. V, TA Pondok Pinang Jakarta 12311	00 62 21 769 71 20	syapetier@fluidra.co.id

	$\sum_{i=1}^{n}$	C)	
ITALY FLUIDRA COMMERCIALE ITALIA	Via Tre Bocche, 7/e Bedizzole, Brescia (ITALY)	00 39 0306870441	info@astralpool.it
KAZAKHSTAN FLUIDRA KAZAKHSTAN	Republic of Kazakhstan, 050059, Almaty City, Bostandyk district, Al-Farabi avenue, house 17/1, n.p. 16a.	00 7 727 311-15-79	bmikhail@fluidra.kz
MALAYSIA Fluidra malaysia	46 Jalan Prima Saujana 1/1a Prima Saujana 43000 Kajang Selangor (MALAYSIA)	00 60 387341030	info@fluidra.com.my
MEXICO FLUIDRA MEXICO	Margarita Maza de Juárez no6, lote 18 Fraccionamiento industrial los Reyes Tlalnepantla, Edo de Méxic	00 52 555 5715 7777	fluidramexico@fluidra.mx
MIDDLE EAST FLUIDRA MIDDLE EAST	PLOT no MO-0715 P.O. BOX 61020 JEBEL ALI FREE ZONE DUBAI U.A.E	00 9714 883 5505	info@fluidrame.com
MONTENEGRO FLUIDRA MONTENEGRO	Cvijetna 27 81000 Podgorica (MONTENEGRO)	00 382 20651188	vdjurisic@fluidra.me
MOROCCO FLUIDRA MAROC	Boulevard Moulay Slimane Casablanca, Ain Sebaa-Hay Mohammedi, Grand Casablanca	00 212 22672275	sgmach@fluidra.ma
NETHERLANDS FLUIDRA SIBO	Doornhoek 3950 5465 TC Veghel (NL)	00 31 (0)413 - 29 39 18	sales@sibo.nl
POLAND FLUIDRA POLSKA	Aleja Armii Krajowej 61 Wroclaw, Breslavia (POLAND)	00 48 713604930	office@astralpool.pl
PORTUGAL FLUIDRA COMERCIAL PORTUGAL	Rua Alfredo da Silva, 41 Trajouce - Sao Domingos de Rana (PORTUGAL)	00 351 21 444 720	comerical@fluidra.pt
ROMANIA Fluidra romania	Strada Lt. Nicolae Pascu, Sector 3 București, Municipiul București (ROMANIA)	00 40 213481443	kiril@fluidrabalkans.com
RUSSIA atral sng	Krasnoproletarskaya str, 16 buil.2 ent.5 127473 Moscow	7 (495) 665-60-11	info@astralpool.ru
SERBIA FLUIDRA SERBICA	Batajnicki drum bb,14km. 11080 BELGRADE (SERBIA)	00 381 113033305	nzlatanovic@fluidra.rs
SINGAPORE ASIA EXPORT	Fluidra Singapore Pte Itd 81 Ubi Avenue 4 #01-08. UB.One. 408831	00 65 6382 0130	info@fluidra.sg
SOUTH AFRICA FLUIDRA SOUTH AFRICA	Nitor Building, Cnr Commerce Cres East & Dartfield Rd, Eastgate Ext 13, Sandton	011 555 1000	customercare@waterlinx.co.za
SPAIN FLUIDRA COMERCIAL ESPAÑA	Carrer Pintor Velázquez, 10, Polinyà (BARCELONA) ESPAÑA	00 34 937136344	clientes@fluidra.es
SWEDEN FLUIDRA NORDIC	Ekenleden 11A Alvered	00 46 31994100	order@fluidra.se
SWITZERLAND ASTRALPOOL SWITZERLAND	Via Industria, 10 6930 Bedano, Lugano	00 41 919354080	rgaletta@astralpool.ch
THAILAND FLUIDRA THAILAND	110/4 13 Rachathewa, Bangplee samutprakam 10540 Samutprakam	00 66 738 9420 4	info@astralpool.co.th
TURKEY FLUIDRA TURKEY	Aydinli Mah. Birlik Organize Sanayi Bolgesi 1 Nolu Cad. No:3 Tuzla/ Istanbul	00 (90) 216 387 05 56 - 57 - 58	info@fluidra.com.tr
UNITED KINGDOM ASTRALPOOL UK LTD	Units 30-32, Palmerston Business Park PO14 IDJ – Newgate Lane	44 (0) 1329 514000	sales@astralpooluk.com
USA Fluidra USA, LLC	8526 Mallory Road Jacksonville, FL 32220	00 (904) 378-0999	customerservice@fluidra.us
VIETNAM FLUIDRA VIETNAM	31 Nguyễn Thị Thập Tân Hưng Quận 7 Hồ Chí Minh, Vietnam	00 84 8 6684 4280	info@fluidra.vn

Fountain of ideas.



FLUIDRA